

Package ‘RStata’

October 12, 2022

Title A Bit of Glue Between R and Stata

Version 1.1.1

Description A simple R -> Stata interface allowing the user to execute Stata commands (both inline and from a .do file) from R.

URL <http://github.com/lbraglia/RStata>

BugReports <http://github.com/lbraglia/RStata/issues>

Imports foreign, tools, utils

License GPL-3

LazyData true

RoxygenNote 5.0.1

NeedsCompilation no

Author Luca Braglia [aut, cre]

Maintainer Luca Braglia <lbraglia@gmail.com>

Repository CRAN

Date/Publication 2016-10-27 17:40:24

R topics documented:

| | |
|--------------------------|---|
| chooseStataBin | 2 |
| RStata | 2 |
| stata | 2 |

| | |
|--------------|----------|
| Index | 4 |
|--------------|----------|

| | |
|----------------|------------------------------|
| chooseStataBin | <i>Set Stata binary path</i> |
|----------------|------------------------------|

Description

Set Stata binary (among found alternatives) path. These settings are lost when R is closed, therefore you should consider adding a `options("RStata.StataPath")` line in your `.Rprofile`.

Usage

```
chooseStataBin()
```

| | |
|--------|--|
| RStata | <i>A Bit of Glue Between R and Stata</i> |
|--------|--|

Description

A simple R -> Stata interface allowing the user to execute Stata commands (both inline and from a `.do` file) from R.

| | |
|-------|---|
| stata | <i>Send commands to a Stata process</i> |
|-------|---|

Description

Function that sends commands to a Stata process.

Usage

```
stata(src = stop("At least 'src' must be specified"), data.in = NULL,
      data.out = FALSE, stata.path = getOption("RStata.StataPath",
      stop("You need to set up a Stata path; ?chooseStataBin")),
      stata.version = getOption("RStata.StataVersion",
      stop("You need to specify your Stata version")),
      stata.echo = getOption("RStata.StataEcho", TRUE), ...)
```

Arguments

| | |
|---------------|--|
| src | character vector of length 1 (path to .do file) or more (a set of stata commands). See examples. |
| data.in | data.frame to be passed to Stata |
| data.out | logical value. If TRUE, the data at the end of the Stata command are returned to R. |
| stata.path | Stata command to be used |
| stata.version | Version of Stata used |
| stata.echo | logical value. If TRUE stata text output will be printed |
| ... | parameter passed to write.dta |

Examples

```
## Not run:
## Single command
stata("help regress") #<- this won't work in Windows due to needed
# batch mode

## Many commands
stata_src <- '

version 10
set more off
sysuse auto
reg mpg weight

'
stata(stata_src)

## External .do file
stata("foo.do")

## Data input to Stata
x <- data.frame(a = rnorm(3), b = letters[1:3])
stata( "sum a", data.in = x)

## Data output from Stata (eg obtain 'auto' dataset)
auto <- stata("sysuse auto", data.out = TRUE)
head(auto)

## Data input/output
(y <- stata("replace a = 2", data.in = x, data.out = TRUE))

## End(Not run)
```

Index

`chooseStataBin`, [2](#)

`data.frame`, [3](#)

`RStata`, [2](#)

`RStata-package (RStata)`, [2](#)

`stata`, [2](#)

`write.dta`, [3](#)