

# Package ‘FSelector’

August 22, 2023

**Type** Package

**Title** Selecting Attributes

**Version** 0.34

**Date** 2023-08-22

**Author** Piotr Romanski, Lars Kotthoff, Patrick Schratz

**Maintainer** Lars Kotthoff <larsko@uwo.edu>

**BugReports** <https://github.com/larskotthoff/fselector/issues>

**URL** <https://github.com/larskotthoff/fselector>

**Description** Functions for selecting attributes from a given dataset. Attribute subset selection is the process of identifying and removing as much of the irrelevant and redundant information as possible.

**License** GPL-2

**Imports** digest, entropy, randomForest, RWeka

**Suggests** mlbench, rpart

**Encoding** UTF-8

**LazyLoad** yes

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2023-08-22 17:10:02 UTC

## R topics documented:

FSelector-package . . . . .	2
as.simple.formula . . . . .	2
best.first.search . . . . .	3
cfs . . . . .	4
chi.squared . . . . .	5
consistency . . . . .	6
correlation . . . . .	7

cutoff . . . . .	8
entropy.based . . . . .	9
exhaustive.search . . . . .	11
greedy.search . . . . .	12
hill.climbing.search . . . . .	13
oneR . . . . .	14
random.forest.importance . . . . .	15
relief . . . . .	16

<b>Index</b>	<b>18</b>
--------------	-----------

---

FSelector-package	<i>Package for selecting attributes</i>
-------------------	---

---

## Description

Package containing functions for selecting attributes from a given dataset and a destination attribute.

## Details

This package contains:

- -Algorithms for filtering attributes: cfs, chi.squared, information.gain, gain.ratio, symmetrical.uncertainty, linear.correlation, rank.correlation, oneR, relief, consistency, random.forest.importance
- -Algorithms for wrapping classifiers and search attribute subset space: best.first.search, backward.search, forward.search, hill.climbing.search
- -Algorithm for choosing a subset of attributes based on attributes' weights: cutoff.k, cutoff.k.percent, cutoff.biggest.diff
- -Algorithm for creating formulas: as.simple.formula

## Author(s)

Piotr Romanski  
 Maintainer: Lars Kotthoff <larsko@uwo.edu>

---

as.simple.formula	<i>Converting to formulas</i>
-------------------	-------------------------------

---

## Description

Converts character vector of attributes' names and destination attribute's name to a simple formula.

## Usage

```
as.simple.formula(attributes, class)
```

**Arguments**

attributes      character vector of attributes' names  
class            name of destination attribute

**Value**

A simple formula like "class ~ attr1 + attr2"

**Author(s)**

Piotr Romanski

**Examples**

```
data(iris)
result <- cfs(Species ~ ., iris)
f <- as.simple.formula(result, "Species")
```

---

best.first.search      *Best-first search*

---

**Description**

The algorithm for searching attribute subset space.

**Usage**

```
best.first.search(attributes, eval.fun, max.backtracks = 5)
```

**Arguments**

attributes      a character vector of all attributes to search in  
eval.fun        a function taking as first parameter a character vector of all attributes and returning a numeric indicating how important a given subset is  
max.backtracks an integer indicating a maximum allowed number of backtracks, default is 5

**Details**

The algorithm is similar to [forward.search](#) besides the fact that it chooses the best node from all already evaluated ones and evaluates it. The selection of the best node is repeated approximately `max.backtracks` times in case no better node found.

**Value**

A character vector of selected attributes.

**Author(s)**

Piotr Romanski

**See Also**[forward.search](#), [backward.search](#), [hill.climbing.search](#), [exhaustive.search](#)**Examples**

```
library(rpart)
data(iris)

evaluator <- function(subset) {
  #k-fold cross validation
  k <- 5
  splits <- runif(nrow(iris))
  results = sapply(1:k, function(i) {
    test.idx <- (splits >= (i - 1) / k) & (splits < i / k)
    train.idx <- !test.idx
    test <- iris[test.idx, , drop=FALSE]
    train <- iris[train.idx, , drop=FALSE]
    tree <- rpart(as.simple.formula(subset, "Species"), train)
    error.rate = sum(test$Species != predict(tree, test, type="c")) / nrow(test)
    return(1 - error.rate)
  })
  print(subset)
  print(mean(results))
  return(mean(results))
}

subset <- best.first.search(names(iris)[-5], evaluator)
f <- as.simple.formula(subset, "Species")
print(f)
```

---

cfs

*CFS filter*

---

**Description**

The algorithm finds attribute subset using correlation and entropy measures for continuous and discrete data.

**Usage**

```
cfs(formula, data)
```

**Arguments**

formula	a symbolic description of a model
data	data to process

**Details**

The algorithm makes use of [best.first.search](#) for searching the attribute subset space.

**Value**

a character vector containing chosen attributes

**Author(s)**

Piotr Romanski

**See Also**

[best.first.search](#)

**Examples**

```
data(iris)

subset <- cfs(Species~., iris)
f <- as.simple.formula(subset, "Species")
print(f)
```

---

chi.squared

*Chi-squared filter*

---

**Description**

The algorithm finds weights of discrete attributes basing on a chi-squared test.

**Usage**

```
chi.squared(formula, data)
```

**Arguments**

formula	a symbolic description of a model
data	a symbolic description of a model

**Details**

The result is equal to Cramer's V coefficient between source attributes and destination attribute.

**Value**

a data.frame containing the worth of attributes in the first column and their names as row names

**Author(s)**

Piotr Romanski

**Examples**

```
library(mlbench)
data(HouseVotes84)

weights <- chi.squared(Class~., HouseVotes84)
print(weights)
subset <- cutoff.k(weights, 5)
f <- as.simple.formula(subset, "Class")
print(f)
```

---

consistency

*Consistency-based filter*

---

**Description**

The algorithm finds attribute subset using consistency measure for continuous and discrete data.

**Usage**

```
consistency(formula, data)
```

**Arguments**

formula	a symbolic description of a model
data	data to process

**Details**

The algorithm makes use of [best.first.search](#) for searching the attribute subset space.

**Value**

a character vector containing chosen attributes

**Author(s)**

Piotr Romanski

**See Also**

[best.first.search](#)

**Examples**

```
## Not run:
library(mlbench)
data(HouseVotes84)

subset <- consistency(Class~., HouseVotes84)
f <- as.simple.formula(subset, "Class")
print(f)

## End(Not run)
```

---

correlation

*Correlation filter*

---

**Description**

The algorithm finds weights of continuous attributes basing on their correlation with continuous class attribute.

**Usage**

```
linear.correlation(formula, data)
rank.correlation(formula, data)
```

**Arguments**

formula	a symbolic description of a model
data	data to process

**Details**

linear.correlation uses Pearson's correlation  
rank.correlation uses Spearman's correlation  
Rows with NA values are not taken into consideration.

**Value**

a data.frame containing the worth of attributes in the first column and their names as row names

**Author(s)**

Piotr Romanski

**Examples**

```

library(mlbench)
data(BostonHousing)
d=BostonHousing[-4] # only numeric variables

weights <- linear.correlation(medv~., d)
print(weights)
subset <- cutoff.k(weights, 3)
f <- as.simple.formula(subset, "medv")
print(f)

weights <- rank.correlation(medv~., d)
print(weights)
subset <- cutoff.k(weights, 3)
f <- as.simple.formula(subset, "medv")
print(f)

```

---

cutoff

*Cutoffs*


---

**Description**

The algorithms select a subset from a ranked attributes.

**Usage**

```

cutoff.k(attrs, k)
cutoff.k.percent(attrs, k)
cutoff.biggest.diff(attrs)

```

**Arguments**

attrs	a data.frame containing ranks for attributes in the first column and their names as row names
k	a positive integer in case of cutoff.k and a numeric between 0 and 1 in case of cutoff.k.percent

**Details**

cutoff.k chooses k best attributes  
cutoff.k.percent chooses best k \* 100% of attributes  
cutoff.biggest.diff chooses a subset of attributes which are significantly better than other.

**Value**

A character vector containing selected attributes.



**Author(s)**

Piotr Romanski

**Examples**

```
data(iris)

weights <- information.gain(Species~., iris)
print(weights)

subset <- cutoff.k(weights, 1)
f <- as.simple.formula(subset, "Species")
print(f)

subset <- cutoff.k.percent(weights, 0.75)
f <- as.simple.formula(subset, "Species")
print(f)

subset <- cutoff.biggest.diff(weights)
f <- as.simple.formula(subset, "Species")
print(f)
```

---

`entropy.based`*Entropy-based filters*

---

**Description**

The algorithms find weights of discrete attributes basing on their correlation with continous class attribute.

**Usage**

```
information.gain(formula, data, unit)
gain.ratio(formula, data, unit)
symmetrical.uncertainty(formula, data, unit)
```

**Arguments**

<code>formula</code>	A symbolic description of a model.
<code>data</code>	Data to process.
<code>unit</code>	Unit for computing entropy (passed to <a href="#">entropy</a> . Default is "log").

**Details**

information.gain is

$$H(Class) + H(Attribute) - H(Class, Attribute)$$

.

gain.ratio is

$$\frac{H(Class) + H(Attribute) - H(Class, Attribute)}{H(Attribute)}$$

symmetrical.uncertainty is

$$2 \frac{H(Class) + H(Attribute) - H(Class, Attribute)}{H(Attribute) + H(Class)}$$

**Value**

a data.frame containing the worth of attributes in the first column and their names as row names

**Author(s)**

Piotr Romanski, Lars Kotthoff

**Examples**

```
data(iris)
```

```
weights <- information.gain(Species~., iris)
print(weights)
subset <- cutoff.k(weights, 2)
f <- as.simple.formula(subset, "Species")
print(f)
```

```
weights <- information.gain(Species~., iris, unit = "log2")
print(weights)
```

```
weights <- gain.ratio(Species~., iris)
print(weights)
subset <- cutoff.k(weights, 2)
f <- as.simple.formula(subset, "Species")
print(f)
```

```
weights <- symmetrical.uncertainty(Species~., iris)
print(weights)
subset <- cutoff.biggest.diff(weights)
f <- as.simple.formula(subset, "Species")
print(f)
```

---

exhaustive.search	<i>Exhaustive search</i>
-------------------	--------------------------

---

**Description**

The algorithm for searching attribute subset space.

**Usage**

```
exhaustive.search(attributes, eval.fun)
```

**Arguments**

attributes	a character vector of all attributes to search in
eval.fun	a function taking as first parameter a character vector of all attributes and returning a numeric indicating how important a given subset is

**Details**

The algorithm searches the whole attribute subset space in breadth-first order.

**Value**

A character vector of selected attributes.

**Author(s)**

Piotr Romanski

**See Also**

[forward.search](#), [backward.search](#), [best.first.search](#), [hill.climbing.search](#)

**Examples**

```
library(rpart)
data(iris)

evaluator <- function(subset) {
  #k-fold cross validation
  k <- 5
  splits <- runif(nrow(iris))
  results = sapply(1:k, function(i) {
    test.idx <- (splits >= (i - 1) / k) & (splits < i / k)
    train.idx <- !test.idx
    test <- iris[test.idx, , drop=FALSE]
    train <- iris[train.idx, , drop=FALSE]
    tree <- rpart(as.simple.formula(subset, "Species"), train)
    error.rate = sum(test$Species != predict(tree, test, type="c")) / nrow(test)
  })
}
```

```
    return(1 - error.rate)
  })
  print(subset)
  print(mean(results))
  return(mean(results))
}

subset <- exhaustive.search(names(iris)[-5], evaluator)
f <- as.simple.formula(subset, "Species")
print(f)
```

---

greedy.search

*Greedy search*

---

## Description

The algorithms for searching attribute subset space.

## Usage

```
backward.search(attributes, eval.fun)
forward.search(attributes, eval.fun)
```

## Arguments

attributes	a character vector of all attributes to search in
eval.fun	a function taking as first parameter a character vector of all attributes and returning a numeric indicating how important a given subset is

## Details

These algorithms implement greedy search. At first, the algorithms expand starting node, evaluate its children and choose the best one which becomes a new starting node. This process goes only in one direction. `forward.search` starts from an empty and `backward.search` from a full set of attributes.

## Value

A character vector of selected attributes.

## Author(s)

Piotr Romanski

## See Also

[best.first.search](#), [hill.climbing.search](#), [exhaustive.search](#)

## Examples

```
library(rpart)
data(iris)

evaluator <- function(subset) {
  #k-fold cross validation
  k <- 5
  splits <- runif(nrow(iris))
  results = sapply(1:k, function(i) {
    test.idx <- (splits >= (i - 1) / k) & (splits < i / k)
    train.idx <- !test.idx
    test <- iris[test.idx, , drop=FALSE]
    train <- iris[train.idx, , drop=FALSE]
    tree <- rpart(as.simple.formula(subset, "Species"), train)
    error.rate = sum(test$Species != predict(tree, test, type="c")) / nrow(test)
    return(1 - error.rate)
  })
  print(subset)
  print(mean(results))
  return(mean(results))
}

subset <- forward.search(names(iris)[-5], evaluator)
f <- as.simple.formula(subset, "Species")
print(f)
```

---

hill.climbing.search    *Hill climbing search*

---

## Description

The algorithm for searching attribute subset space.

## Usage

```
hill.climbing.search(attributes, eval.fun)
```

## Arguments

attributes	a character vector of all attributes to search in
eval.fun	a function taking as first parameter a character vector of all attributes and returning a numeric indicating how important a given subset is

## Details

The algorithm starts with a random attribute set. Then it evaluates all its neighbours and chooses the best one. It might be susceptible to local maximum.

**Value**

A character vector of selected attributes.

**Author(s)**

Piotr Romanski

**See Also**

[forward.search](#), [backward.search](#), [best.first.search](#), [exhaustive.search](#)

**Examples**

```
library(rpart)
data(iris)

evaluator <- function(subset) {
  #k-fold cross validation
  k <- 5
  splits <- runif(nrow(iris))
  results = sapply(1:k, function(i) {
    test.idx <- (splits >= (i - 1) / k) & (splits < i / k)
    train.idx <- !test.idx
    test <- iris[test.idx, , drop=FALSE]
    train <- iris[train.idx, , drop=FALSE]
    tree <- rpart(as.simple.formula(subset, "Species"), train)
    error.rate = sum(test$Species != predict(tree, test, type="c")) / nrow(test)
    return(1 - error.rate)
  })
  print(subset)
  print(mean(results))
  return(mean(results))
}

subset <- hill.climbing.search(names(iris)[-5], evaluator)
f <- as.simple.formula(subset, "Species")
print(f)
```

**Description**

The algorithms find weights of discrete attributes basing on very simple association rules involving only one attribute in condition part.

**Usage**

```
oneR(formula, data)
```

**Arguments**

formula	a symbolic description of a model
data	data to process

**Details**

The algorithm uses OneR classifier to find out the attributes' weights. For each attribute it creates a simple rule based only on that attribute and then calculates its error rate.

**Value**

a data.frame containing the worth of attributes in the first column and their names as row names

**Author(s)**

Piotr Romanski

**Examples**

```
library(mlbench)
data(HouseVotes84)

weights <- oneR(Class~., HouseVotes84)
print(weights)
subset <- cutoff.k(weights, 5)
f <- as.simple.formula(subset, "Class")
print(f)
```

---

random.forest.importance

*RandomForest filter*

---

**Description**

The algorithm finds weights of attributes using RandomForest algorithm.

**Usage**

```
random.forest.importance(formula, data, importance.type = 1)
```

**Arguments**

formula	a symbolic description of a model
data	data to process
importance.type	either 1 or 2, specifying the type of importance measure (1=mean decrease in accuracy, 2=mean decrease in node impurity)

**Details**

This is a wrapper for [importance](#).

**Value**

a data.frame containing the worth of attributes in the first column and their names as row names

**Author(s)**

Piotr Romanski

**Examples**

```
library(mlbench)
data(HouseVotes84)

weights <- random.forest.importance(Class~., HouseVotes84, importance.type = 1)
print(weights)
subset <- cutoff.k(weights, 5)
f <- as.simple.formula(subset, "Class")
print(f)
```

---

relief

*RReliefF filter*


---

**Description**

The algorithm finds weights of continuous and discrete attributes basing on a distance between instances.

**Usage**

```
relief(formula, data, neighbours.count = 5, sample.size = 10)
```

**Arguments**

formula	a symbolic description of a model
data	data to process
neighbours.count	number of neighbours to find for every sampled instance
sample.size	number of instances to sample



**Details**

The algorithm samples instances and finds their nearest hits and misses. Considering that result, it evaluates weights of attributes.

**Value**

a data.frame containing the worth of attributes in the first column and their names as row names

**Author(s)**

Piotr Romanski

**References**

- -Igor Kononenko: Estimating Attributes: Analysis and Extensions of RELIEF. In: European Conference on Machine Learning, 171-182, 1994.
- -Marko Robnik-Sikonja, Igor Kononenko: An adaptation of Relief for attribute estimation in regression. In: Fourteenth International Conference on Machine Learning, 296-304, 1997.

**Examples**

```
data(iris)

weights <- relief(Species~., iris, neighbours.count = 5, sample.size = 20)
print(weights)
subset <- cutoff.k(weights, 2)
f <- as.simple.formula(subset, "Species")
print(f)
```

# Index

## \* package

FSelector-package, 2

as.simple.formula, 2

backward.search, 4, 11, 14

backward.search (greedy.search), 12

best.first.search, 3, 5, 6, 11, 12, 14

cfs, 4

chi.squared, 5

consistency, 6

correlation, 7

cutoff, 8

entropy, 9

entropy.based, 9

exhaustive.search, 4, 11, 12, 14

forward.search, 3, 4, 11, 14

forward.search (greedy.search), 12

FSelector (FSelector-package), 2

FSelector-package, 2

gain.ratio (entropy.based), 9

greedy.search, 12

hill.climbing.search, 4, 11, 12, 13

importance, 16

information.gain (entropy.based), 9

linear.correlation (correlation), 7

oneR, 14

random.forest.importance, 15

rank.correlation (correlation), 7

relief, 16

symmetrical.uncertainty  
(entropy.based), 9