

Package ‘paws.machine.learning’

May 10, 2024

Title 'Amazon Web Services' Machine Learning Services

Version 0.6.0

Description Interface to 'Amazon Web Services' machine learning services, including 'SageMaker' managed machine learning service, natural language processing, speech recognition, translation, and more
<https://aws.amazon.com/machine-learning/>.

License Apache License (>= 2.0)

URL <https://github.com/paws-r/paws>

BugReports <https://github.com/paws-r/paws/issues>

Imports paws.common (>= 0.6.0)

Suggests testthat

Encoding UTF-8

RoxigenNote 7.3.1

Collate 'augmentedairuntime_service.R'
'augmentedairuntime_interfaces.R'
'augmentedairuntime_operations.R' 'bedrock_service.R'
'bedrock_interfaces.R' 'bedrock_operations.R'
'bedrockruntime_service.R' 'bedrockruntime_interfaces.R'
'bedrockruntime_operations.R' 'comprehend_service.R'
'comprehend_interfaces.R' 'comprehend_operations.R'
'comprehendmedical_service.R' 'comprehendmedical_interfaces.R'
'comprehendmedical_operations.R' 'elasticinference_service.R'
'elasticinference_interfaces.R' 'elasticinference_operations.R'
'forecastqueryservice_service.R'
'forecastqueryservice_interfaces.R'
'forecastqueryservice_operations.R' 'forecastservice_service.R'
'forecastservice_interfaces.R' 'forecastservice_operations.R'
'frauddetector_service.R' 'frauddetector_interfaces.R'
'frauddetector_operations.R'
'lexmodelbuildingservice_service.R'
'lexmodelbuildingservice_interfaces.R'
'lexmodelbuildingservice_operations.R' 'lexmodelsv2_service.R'

```
'lexmodelsv2_interfaces.R' 'lexmodelsv2_operations.R'
'lexruntimeservice_service.R' 'lexruntimeservice_interfaces.R'
'lexruntimeservice_operations.R' 'lexruntimev2_service.R'
'lexruntimev2_interfaces.R' 'lexruntimev2_operations.R'
'lookoutequipment_service.R' 'lookoutequipment_interfaces.R'
'lookoutequipment_operations.R' 'lookoutmetrics_service.R'
'lookoutmetrics_interfaces.R' 'lookoutmetrics_operations.R'
'machinelearning_service.R' 'machinelearning_interfaces.R'
'machinelearning_operations.R' 'panorama_service.R'
'panorama_interfaces.R' 'panorama_operations.R'
'personalize_service.R' 'personalize_interfaces.R'
'personalize_operations.R' 'personalizeevents_service.R'
'personalizeevents_interfaces.R'
'personalizeevents_operations.R' 'personalizeruntime_service.R'
'personalizeruntime_interfaces.R'
'personalizeruntime_operations.R' 'polly_service.R'
'polly_interfaces.R' 'polly_operations.R'
'reexports_paws.common.R' 'rekognition_service.R'
'rekognition_interfaces.R' 'rekognition_operations.R'
'sagemaker_service.R' 'sagemaker_interfaces.R'
'sagemaker_operations.R' 'sagemakeredgemanager_service.R'
'sagemakeredgemanager_interfaces.R'
'sagemakeredgemanager_operations.R'
'sagemakerfeaturestoreruntime_service.R'
'sagemakerfeaturestoreruntime_interfaces.R'
'sagemakerfeaturestoreruntime_operations.R'
'sagemakergeospatialcapabilities_service.R'
'sagemakergeospatialcapabilities_interfaces.R'
'sagemakergeospatialcapabilities_operations.R'
'sagemakermetrics_service.R' 'sagemakermetrics_interfaces.R'
'sagemakermetrics_operations.R' 'sagemakerruntime_service.R'
'sagemakerruntime_interfaces.R' 'sagemakerruntime_operations.R'
'textract_service.R' 'textract_interfaces.R'
'textract_operations.R' 'transcribeservice_service.R'
'transcribeservice_interfaces.R'
'transcribeservice_operations.R' 'translate_service.R'
'translate_interfaces.R' 'translate_operations.R'
'veoiceid_service.R' 'voiceid_interfaces.R'
'veoiceid_operations.R'
```

NeedsCompilation no

Author David Kretch [aut],

Adam Banker [aut],

Dyfan Jones [cre],

Amazon.com, Inc. [cph]

Maintainer Dyfan Jones <dyfan.r.jones@gmail.com>

Repository CRAN

Date/Publication 2024-05-10 16:30:02 UTC

R topics documented:

augmentedairuntime	3
bedrock	6
bedrockruntime	9
comprehend	11
comprehendmedical	15
elasticinference	18
forecastqueryservice	21
forecastservice	23
frauddetector	26
lexmodelbuildingservice	30
lexmodelsv2	33
lexruntimeservice	38
lexruntimev2	40
lookoutequipment	43
lookoutmetrics	46
machinelearning	49
panorama	52
personalize	54
personalizeevents	58
personalizeruntime	60
polly	63
rekognition	65
sagemaker	71
sagemakeredgemanager	80
sagemakerfeaturerestoreruntime	82
sagemakergeospatialcapabilities	86
sagemakermetrics	89
sagemakerruntime	91
textract	93
transcribeservice	96
translate	99
voiceid	102

Index

105

augmentedairuntime *Amazon Augmented AI Runtime*

Description

Amazon Augmented AI (Amazon A2I) adds the benefit of human judgment to any machine learning application. When an AI application can't evaluate data with a high degree of confidence, human reviewers can take over. This human review is called a human review workflow. To create and start a human review workflow, you need three resources: a *worker task template*, a *flow definition*, and a *human loop*.

For information about these resources and prerequisites for using Amazon A2I, see [Get Started with Amazon Augmented AI](#) in the Amazon SageMaker Developer Guide.

This API reference includes information about API actions and data types that you can use to interact with Amazon A2I programmatically. Use this guide to:

- Start a human loop with the `start_human_loop` operation when using Amazon A2I with a *custom task type*. To learn more about the difference between custom and built-in task types, see [Use Task Types](#). To learn how to start a human loop using this API, see [Create and Start a Human Loop for a Custom Task Type](#) in the Amazon SageMaker Developer Guide.
- Manage your human loops. You can list all human loops that you have created, describe individual human loops, and stop and delete human loops. To learn more, see [Monitor and Manage Your Human Loop](#) in the Amazon SageMaker Developer Guide.

Amazon A2I integrates APIs from various AWS services to create and start human review workflows for those services. To learn how Amazon A2I uses these APIs, see [Use APIs in Amazon A2I](#) in the Amazon SageMaker Developer Guide.

Usage

```
augmentedairuntime(
    config = list(),
    credentials = list(),
    endpoint = NULL,
    region = NULL
)
```

Arguments

<code>config</code>	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoints.html
---------------------	---

credentials	Optional credentials shorthand for the config parameter
	<ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- augmentedairuntime(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
```

```
    region = "string"
)
```

Operations

delete_human_loop	Deletes the specified human loop for a flow definition
describe_human_loop	Returns information about the specified human loop
list_human_loops	Returns information about human loops, given the specified parameters
start_human_loop	Starts a human loop, provided that at least one activation condition is met
stop_human_loop	Stops the specified human loop

Examples

```
## Not run:
svc <- augmentedairuntime()
svc$delete_human_loop(
  Foo = 123
)
## End(Not run)
```

bedrock

Amazon Bedrock

Description

Describes the API operations for creating, managing, fine-turning, and evaluating Amazon Bedrock models.

Usage

```
bedrock(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

- | | |
|---------------|---|
| config | Optional configuration of credentials, endpoint, and/or region. |
|---------------|---|
- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.

	<ul style="list-style-type: none"> – anonymous: Set anonymous credentials.
	<ul style="list-style-type: none"> • endpoint: The complete URL to use for the constructed client.
	<ul style="list-style-type: none"> • region: The AWS Region used in instantiating the client.
	<ul style="list-style-type: none"> • close_connection: Immediately close all HTTP connections.
	<ul style="list-style-type: none"> • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.
	<ul style="list-style-type: none"> • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>.
	<ul style="list-style-type: none"> • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
<code>credentials</code>	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
<code>endpoint</code>	Optional shorthand for complete URL to use for the constructed client.
<code>region</code>	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- bedrock(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
  )
)
```

```

        stsRegionalEndpoint = "string"
    ),
    credentials = list(
        creds = list(
            accessKeyId = "string",
            secretAccessKey = "string",
            sessionToken = "string"
        ),
        profile = "string",
        anonymous = "logical"
    ),
    endpoint = "string",
    region = "string"
)

```

Operations

create_evaluation_job	API operation for creating and managing Amazon Bedrock automatic model evaluation jobs.
create_guardrail	Creates a guardrail to block topics and to filter out harmful content.
create_guardrail_version	Creates a version of the guardrail.
create_model_customization_job	Creates a fine-tuning job to customize a base model.
create_provisioned_model_throughput	Creates dedicated throughput for a base or custom model with the model usage limit.
delete_custom_model	Deletes a custom model that you created earlier.
delete_guardrail	Deletes a guardrail.
delete_model_invocation_logging_configuration	Deletes the invocation logging configuration.
delete_provisioned_model_throughput	Deletes a Provisioned Throughput.
get_custom_model	Get the properties associated with a Amazon Bedrock custom model that you created.
get_evaluation_job	Retrieves the properties associated with a model evaluation job, including the status.
get.foundation_model	Get details about a Amazon Bedrock foundation model.
get.guardrail	Gets details about a guardrail.
get.model_customization_job	Retrieves the properties associated with a model-customization job, including the status.
get.model_invocation_logging_configuration	Get the current configuration values for model invocation logging.
get.provisioned_model_throughput	Returns details for a Provisioned Throughput.
list_custom_models	Returns a list of the custom models that you have created with the CreateCustomModel operation.
list_evaluation_jobs	Lists model evaluation jobs.
list.foundation_models	Lists Amazon Bedrock foundation models that you can use.
list.guardrails	Lists details about all the guardrails in an account.
list.model_customization_jobs	Returns a list of model customization jobs that you have submitted.
list.provisioned_model_throughputs	Lists the Provisioned Throughputs in the account.
list.tags_for_resource	List the tags associated with the specified resource.
put.model_invocation_logging_configuration	Set the configuration values for model invocation logging.
stop_evaluation_job	Stops an in progress model evaluation job.
stop_model_customization_job	Stops an active model customization job.
tag_resource	Associate tags with a resource.
untag_resource	Remove one or more tags from a resource.
update.guardrail	Updates a guardrail with the values you specify.
update_provisioned_model_throughput	Updates the name or associated model for a Provisioned Throughput.

Examples

```
## Not run:  
svc <- bedrock()  
svc$create_evaluation_job(  
  Foo = 123  
)  
  
## End(Not run)
```

bedrockruntime

Amazon Bedrock Runtime

Description

Describes the API operations for running inference using Amazon Bedrock models.

Usage

```
bedrockruntime(  
  config = list(),  
  credentials = list(),  
  endpoint = NULL,  
  region = NULL  
)
```

Arguments

- | | |
|--------|--|
| config | Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none">• credentials:<ul style="list-style-type: none">– creds:<ul style="list-style-type: none">* access_key_id: AWS access key ID* secret_access_key: AWS secret access key* session_token: AWS temporary session token– profile: The name of a profile to use. If not given, then the default profile is used.– anonymous: Set anonymous credentials.• endpoint: The complete URL to use for the constructed client.• region: The AWS Region used in instantiating the client.• close_connection: Immediately close all HTTP connections.• timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. |
|--------|--|

	<ul style="list-style-type: none"> • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- bedrockruntime(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    )
  )
)
```

```
  ),
  profile = "string",
  anonymous = "logical"
),
endpoint = "string",
region = "string"
)
```

Operations

[invoke_model](#)
[invoke_model_with_response_stream](#)

Invokes the specified Amazon Bedrock model to run inference using the prompt and invoke the specified Amazon Bedrock model to run inference using the prompt and in

Examples

```
## Not run:
svc <- bedrockruntime()
svc$invoke_model(
  Foo = 123
)

## End(Not run)
```

Description

Amazon Comprehend is an Amazon Web Services service for gaining insight into the content of documents. Use these actions to determine the topics contained in your documents, the topics they discuss, the predominant sentiment expressed in them, the predominant language used, and more.

Usage

```
comprehend(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region.
	<ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized.html
credentials	Optional credentials shorthand for the config parameter
	<ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- comprehend(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",

```

```

        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
stsRegionalEndpoint = "string"
),
credentials = list(
    creds = list(
        accessKeyId = "string",
        secretAccessKey = "string",
        sessionToken = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

batch_detect_dominant_language	Determines the dominant language of the input text for a batch of documents
batch_detect_entities	Inspects the text of a batch of documents for named entities and returns information about them
batch_detect_key_phrases	Detects the key noun phrases found in a batch of documents
batch_detect_sentiment	Inspects a batch of documents and returns an inference of the prevailing sentiment
batch_detect_syntax	Inspects the text of a batch of documents for the syntax and part of speech of the words
batch_detect_targeted_sentiment	Inspects a batch of documents and returns a sentiment analysis for each entity in the document
classify_document	Creates a classification request to analyze a single document in real-time
contains_pii_entities	Analyzes input text for the presence of personally identifiable information (PII)
create_dataset	Creates a dataset to upload training or test data for a model associated with a flywheel
create_document_classifier	Creates a new document classifier that you can use to categorize documents
create_endpoint	Creates a model-specific endpoint for synchronous inference for a previously trained model
create_entity_recognizer	Creates an entity recognizer using submitted files
create_flywheel	A flywheel is an Amazon Web Services resource that orchestrates the ongoing training of machine learning models
delete_document_classifier	Deletes a previously created document classifier
delete_endpoint	Deletes a model-specific endpoint for a previously-trained custom model
delete_entity_recognizer	Deletes an entity recognizer
delete_flywheel	Deletes a flywheel
delete_resource_policy	Deletes a resource-based policy that is attached to a custom model
describe_dataset	Returns information about the dataset that you specify
describe_document_classification_job	Gets the properties associated with a document classification job

<code>describe_document_classifier</code>	Gets the properties associated with a document classifier
<code>describe_dominant_language_detection_job</code>	Gets the properties associated with a dominant language detection job
<code>describe_endpoint</code>	Gets the properties associated with a specific endpoint
<code>describe_entities_detection_job</code>	Gets the properties associated with an entities detection job
<code>describe_entity_recognizer</code>	Provides details about an entity recognizer including status, S3 buckets containing training data, and configuration information
<code>describe_events_detection_job</code>	Gets the status and details of an events detection job
<code>describe_flywheel</code>	Provides configuration information about the flywheel
<code>describe_flywheel_iteration</code>	Retrieve the configuration properties of a flywheel iteration
<code>describe_key_phrases_detection_job</code>	Gets the properties associated with a key phrases detection job
<code>describe_pii_entities_detection_job</code>	Gets the properties associated with a PII entities detection job
<code>describe_resource_policy</code>	Gets the details of a resource-based policy that is attached to a custom model, including the ARN of the policy and the ARN of the custom model
<code>describe_sentiment_detection_job</code>	Gets the properties associated with a sentiment detection job
<code>describe_targeted_sentiment_detection_job</code>	Gets the properties associated with a targeted sentiment detection job
<code>describe_topics_detection_job</code>	Gets the properties associated with a topic detection job
<code>detect_dominant_language</code>	Determines the dominant language of the input text
<code>detect_entities</code>	Detects named entities in input text when you use the pre-trained model
<code>detect_key_phrases</code>	Detects the key noun phrases found in the text
<code>detect_pii_entities</code>	Inspects the input text for entities that contain personally identifiable information (PII)
<code>detect_sentiment</code>	Inspects text and returns an inference of the prevailing sentiment (POSITIVE, NEGATIVE, or NEUTRAL)
<code>detect_syntax</code>	Inspects text for syntax and the part of speech of words in the document
<code>detect_targeted_sentiment</code>	Inspects the input text and returns a sentiment analysis for each entity identified
<code>detect_toxic_content</code>	Performs toxicity analysis on the list of text strings that you provide as input
<code>import_model</code>	Creates a new custom model that replicates a source custom model that you import
<code>list_datasets</code>	List the datasets that you have configured in this Region
<code>list_document_classification_jobs</code>	Gets a list of the documentation classification jobs that you have submitted
<code>list_document_classifiers</code>	Gets a list of the document classifiers that you have created
<code>list_document_classifier_summaries</code>	Gets a list of summaries of the document classifiers that you have created
<code>list_dominant_language_detection_jobs</code>	Gets a list of the dominant language detection jobs that you have submitted
<code>list_endpoints</code>	Gets a list of all existing endpoints that you've created
<code>list_entities_detection_jobs</code>	Gets a list of the entity detection jobs that you have submitted
<code>list_entity_recognizers</code>	Gets a list of the properties of all entity recognizers that you created, including the ARN of the recognizer and the ARN of the custom model
<code>list_entity_recognizer_summaries</code>	Gets a list of summaries for the entity recognizers that you have created
<code>list_events_detection_jobs</code>	Gets a list of the events detection jobs that you have submitted
<code>list_flywheel_iteration_history</code>	Information about the history of a flywheel iteration
<code>list_flywheels</code>	Gets a list of the flywheels that you have created
<code>list_key_phrases_detection_jobs</code>	Get a list of key phrase detection jobs that you have submitted
<code>list_pii_entities_detection_jobs</code>	Gets a list of the PII entity detection jobs that you have submitted
<code>list_sentiment_detection_jobs</code>	Gets a list of sentiment detection jobs that you have submitted
<code>list_tags_for_resource</code>	Lists all tags associated with a given Amazon Comprehend resource
<code>list_targeted_sentiment_detection_jobs</code>	Gets a list of targeted sentiment detection jobs that you have submitted
<code>list_topics_detection_jobs</code>	Gets a list of the topic detection jobs that you have submitted
<code>put_resource_policy</code>	Attaches a resource-based policy to a custom model
<code>start_document_classification_job</code>	Starts an asynchronous document classification job using a custom classification model
<code>start_dominant_language_detection_job</code>	Starts an asynchronous dominant language detection job for a collection of documents
<code>start_entities_detection_job</code>	Starts an asynchronous entity detection job for a collection of documents
<code>start_events_detection_job</code>	Starts an asynchronous event detection job for a collection of documents
<code>start_flywheel_iteration</code>	Starts the flywheel iteration
<code>start_key_phrases_detection_job</code>	Starts an asynchronous key phrase detection job for a collection of documents

start_pii_entities_detection_job	Starts an asynchronous PII entity detection job for a collection of documents
start_sentiment_detection_job	Starts an asynchronous sentiment detection job for a collection of documents
start_targeted_sentiment_detection_job	Starts an asynchronous targeted sentiment detection job for a collection of documents
start_topics_detection_job	Starts an asynchronous topic detection job
stop_dominant_language_detection_job	Stops a dominant language detection job in progress
stop_entities_detection_job	Stops an entities detection job in progress
stop_events_detection_job	Stops an events detection job in progress
stop_key_phrases_detection_job	Stops a key phrases detection job in progress
stop_pii_entities_detection_job	Stops a PII entities detection job in progress
stop_sentiment_detection_job	Stops a sentiment detection job in progress
stop_targeted_sentiment_detection_job	Stops a targeted sentiment detection job in progress
stop_training_document_classifier	Stops a document classifier training job while in progress
stop_training_entity_recognizer	Stops an entity recognizer training job while in progress
tag_resource	Associates a specific tag with an Amazon Comprehend resource
untag_resource	Removes a specific tag associated with an Amazon Comprehend resource
update_endpoint	Updates information about the specified endpoint
update_flywheel	Update the configuration information for an existing flywheel

Examples

```
## Not run:
svc <- comprehend()
svc$batch_detect_dominant_language(
  Foo = 123
)
## End(Not run)
```

Description

Amazon Comprehend Medical extracts structured information from unstructured clinical text. Use these actions to gain insight in your documents. Amazon Comprehend Medical only detects entities in English language texts. Amazon Comprehend Medical places limits on the sizes of files allowed for different API operations. To learn more, see [Guidelines and quotas](#) in the *Amazon Comprehend Medical Developer Guide*.

Usage

```
comprehendmedical(
  config = list(),
  credentials = list(),
```

```

    endpoint = NULL,
    region = NULL
)

```

Arguments

config	Optional configuration of credentials, endpoint, and/or region.
	<ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized.html
credentials	Optional credentials shorthand for the config parameter
	<ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```

svc <- comprehendmedical(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)

```

Operations

describe_entities_detection_v2_job	Gets the properties associated with a medical entities detection job
describe_icd10cm_inference_job	Gets the properties associated with an InferICD10CM job
describe_phi_detection_job	Gets the properties associated with a protected health information (PHI) detection job
describe_rx_norm_inference_job	Gets the properties associated with an InferRxNorm job
describe_snomedct_inference_job	Gets the properties associated with an InferSNOMEDCT job
detect_entities	The DetectEntities operation is deprecated
detect_entities_v2	Inspects the clinical text for a variety of medical entities and returns specific information
detect_phi	Inspects the clinical text for protected health information (PHI) entities and returns the entities
infer_icd10cm	InferICD10CM detects medical conditions as entities listed in a patient record and links them to the ICD-10-CM codes
infer_rx_norm	InferRxNorm detects medications as entities listed in a patient record and links to the National Drug Code Database (NDC)
infer_snomedct	InferSNOMEDCT detects possible medical concepts as entities and links them to codes in the SNOMED CT database
list_entities_detection_v2_jobs	Gets a list of medical entity detection jobs that you have submitted
list_icd10cm_inference_jobs	Gets a list of InferICD10CM jobs that you have submitted
list_phi_detection_jobs	Gets a list of protected health information (PHI) detection jobs you have submitted

<code>list_rx_norm_inference_jobs</code>	Gets a list of InferRxNorm jobs that you have submitted
<code>list_snomedct_inference_jobs</code>	Gets a list of InferSNOMEDCT jobs a user has submitted
<code>start_entities_detection_v2_job</code>	Starts an asynchronous medical entity detection job for a collection of documents
<code>start_icd10cm_inference_job</code>	Starts an asynchronous job to detect medical conditions and link them to the ICD-10-CM
<code>start_phi_detection_job</code>	Starts an asynchronous job to detect protected health information (PHI)
<code>start_rx_norm_inference_job</code>	Starts an asynchronous job to detect medication entities and link them to the RxNorm on
<code>start_snomedct_inference_job</code>	Starts an asynchronous job to detect medical concepts and link them to the SNOMED-CT
<code>stop_entities_detection_v2_job</code>	Stops a medical entities detection job in progress
<code>stop_icd10cm_inference_job</code>	Stops an InferICD10CM inference job in progress
<code>stop_phi_detection_job</code>	Stops a protected health information (PHI) detection job in progress
<code>stop_rx_norm_inference_job</code>	Stops an InferRxNorm inference job in progress
<code>stop_snomedct_inference_job</code>	Stops an InferSNOMEDCT inference job in progress

Examples

```
## Not run:
svc <- comprehendmedical()
svc$describe_entities_detection_v2_job(
  Foo = 123
)

## End(Not run)
```

Description

Elastic Inference public APIs.

February 15, 2023: Starting April 15, 2023, AWS will not onboard new customers to Amazon Elastic Inference (EI), and will help current customers migrate their workloads to options that offer better price and performance. After April 15, 2023, new customers will not be able to launch instances with Amazon EI accelerators in Amazon SageMaker, Amazon ECS, or Amazon EC2. However, customers who have used Amazon EI at least once during the past 30-day period are considered current customers and will be able to continue using the service.

Usage

```
elasticinference(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region.
	<ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized.html
credentials	Optional credentials shorthand for the config parameter
	<ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- elasticinference(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",

```

```

    secret_access_key = "string",
    session_token = "string"
),
profile = "string",
anonymous = "logical"
),
endpoint = "string",
region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
stsRegionalEndpoint = "string"
),
credentials = list(
  creds = list(
    accessKeyId = "string",
    secretAccessKey = "string",
    sessionToken = "string"
),
profile = "string",
anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

<code>describe_accelerator_offerings</code>	Describes the locations in which a given accelerator type or set of types is present in a given region.
<code>describe_accelerators</code>	Describes information over a provided set of accelerators belonging to an account.
<code>describe_accelerator_types</code>	Describes the accelerator types available in a given region, as well as their characteristics, such as memory and compute.
<code>list_tags_for_resource</code>	Returns all tags of an Elastic Inference Accelerator.
<code>tag_resource</code>	Adds the specified tags to an Elastic Inference Accelerator.
<code>untag_resource</code>	Removes the specified tags from an Elastic Inference Accelerator.

Examples

```

## Not run:
svc <- elasticinference()
svc$describe_accelerator_offerings(
  Foo = 123
)

## End(Not run)

```

forecastqueryservice *Amazon Forecast Query Service*

Description

Provides APIs for creating and managing Amazon Forecast resources.

Usage

```
forecastqueryservice(  
    config = list(),  
    credentials = list(),  
    endpoint = NULL,  
    region = NULL  
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none">• credentials:<ul style="list-style-type: none">– creds:<ul style="list-style-type: none">* access_key_id: AWS access key ID* secret_access_key: AWS secret access key* session_token: AWS temporary session token– profile: The name of a profile to use. If not given, then the default profile is used.– anonymous: Set anonymous credentials.• endpoint: The complete URL to use for the constructed client.• region: The AWS Region used in instantiating the client.• close_connection: Immediately close all HTTP connections.• timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.• s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>.• stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none">• creds:<ul style="list-style-type: none">– access_key_id: AWS access key ID– secret_access_key: AWS secret access key– session_token: AWS temporary session token• profile: The name of a profile to use. If not given, then the default profile is used.

- **anonymous:** Set anonymous credentials.

endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- forecastqueryservice(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

<code>query_forecast</code>	Retrieves a forecast for a single item, filtered by the supplied criteria
<code>query_what_if_forecast</code>	Retrieves a what-if forecast

Examples

```
## Not run:  
svc <- forecastqueryservice()  
svc$query_forecast(  
  Foo = 123  
)  
  
## End(Not run)
```

forecastservice	<i>Amazon Forecast Service</i>
-----------------	--------------------------------

Description

Provides APIs for creating and managing Amazon Forecast resources.

Usage

```
forecastservice(  
  config = list(),  
  credentials = list(),  
  endpoint = NULL,  
  region = NULL  
)
```

Arguments

- | | |
|--------|--|
| config | Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none">• credentials:<ul style="list-style-type: none">– creds:<ul style="list-style-type: none">* access_key_id: AWS access key ID* secret_access_key: AWS secret access key* session_token: AWS temporary session token– profile: The name of a profile to use. If not given, then the default profile is used.– anonymous: Set anonymous credentials.• endpoint: The complete URL to use for the constructed client.• region: The AWS Region used in instantiating the client.• close_connection: Immediately close all HTTP connections.• timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. |
|--------|--|

	<ul style="list-style-type: none"> • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- forecastservice(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    )
  )
)
```

```
        ),
        profile = "string",
        anonymous = "logical"
    ),
    endpoint = "string",
    region = "string"
)
```

Operations

create_auto_predictor	Creates an Amazon Forecast predictor
create_dataset	Creates an Amazon Forecast dataset
create_dataset_group	Creates a dataset group, which holds a collection of related datasets
create_dataset_import_job	Imports your training data to an Amazon Forecast dataset
create_explainability	Explainability is only available for Forecasts and Predictors generated from an Auto
create_explainability_export	Exports an Explainability resource created by the CreateExplainability operation
create_forecast	Creates a forecast for each item in the TARGET_TIME_SERIES dataset that was u
create_forecast_export_job	Exports a forecast created by the CreateForecast operation to your Amazon Simple
create_monitor	Creates a predictor monitor resource for an existing auto predictor
create_predictor	This operation creates a legacy predictor that does not include all the predictor func
create_predictor_backtest_export_job	Exports backtest forecasts and accuracy metrics generated by the CreateAutoPredic
create_what_if_analysis	What-if analysis is a scenario modeling technique where you make a hypothetical c
create_what_if_forecast	A what-if forecast is a forecast that is created from a modified version of the baselin
create_what_if_forecast_export	Exports a forecast created by the CreateWhatIfForecast operation to your Amazon S
delete_dataset	Deletes an Amazon Forecast dataset that was created using the CreateDataset opera
delete_dataset_group	Deletes a dataset group created using the CreateDatasetGroup operation
delete_dataset_import_job	Deletes a dataset import job created using the CreateDatasetImportJob operation
delete_explainability	Deletes an Explainability resource
delete_explainability_export	Deletes an Explainability export
delete_forecast	Deletes a forecast created using the CreateForecast operation
delete_forecast_export_job	Deletes a forecast export job created using the CreateForecastExportJob operation
delete_monitor	Deletes a monitor resource
delete_predictor	Deletes a predictor created using the DescribePredictor or CreatePredictor operation
delete_predictor_backtest_export_job	Deletes a predictor backtest export job
delete_resource_tree	Deletes an entire resource tree
delete_what_if_analysis	Deletes a what-if analysis created using the CreateWhatIfAnalysis operation
delete_what_if_forecast	Deletes a what-if forecast created using the CreateWhatIfForecast operation
delete_what_if_forecast_export	Deletes a what-if forecast export created using the CreateWhatIfForecastExport ope
describe_auto_predictor	Describes a predictor created using the CreateAutoPredictor operation
describe_dataset	Describes an Amazon Forecast dataset created using the CreateDataset operation
describe_dataset_group	Describes a dataset group created using the CreateDatasetGroup operation
describe_dataset_import_job	Describes a dataset import job created using the CreateDatasetImportJob operation
describe_explainability	Describes an Explainability resource created using the CreateExplainability operati
describe_explainability_export	Describes an Explainability export created using the CreateExplainabilityExport op
describe_forecast	Describes a forecast created using the CreateForecast operation
describe_forecast_export_job	Describes a forecast export job created using the CreateForecastExportJob operation
describe_monitor	Describes a monitor resource
describe_predictor	This operation is only valid for legacy predictors created with CreatePredictor

describe_predictor_backtest_export_job	Describes a predictor backtest export job created using the CreatePredictorBacktestExport operation.
describe_what_if_analysis	Describes the what-if analysis created using the CreateWhatIfAnalysis operation.
describe_what_if_forecast	Describes the what-if forecast created using the CreateWhatIfForecast operation.
describe_what_if_forecast_export	Describes the what-if forecast export created using the CreateWhatIfForecastExport operation.
get_accuracy_metrics	Provides metrics on the accuracy of the models that were trained by the CreatePredictor operation.
list_dataset_groups	Returns a list of dataset groups created using the CreateDatasetGroup operation.
list_dataset_import_jobs	Returns a list of dataset import jobs created using the CreateDatasetImportJob operation.
list_datasets	Returns a list of datasets created using the CreateDataset operation.
list_explainabilities	Returns a list of Explainability resources created using the CreateExplainability operation.
list_explainability_exports	Returns a list of Explainability exports created using the CreateExplainabilityExport operation.
list_forecast_export_jobs	Returns a list of forecast export jobs created using the CreateForecastExportJob operation.
list_forecasts	Returns a list of forecasts created using the CreateForecast operation.
list_monitor_evaluations	Returns a list of the monitoring evaluation results and predictor events collected by the CreateMonitor operation.
list_monitors	Returns a list of monitors created with the CreateMonitor operation and CreateAutoMonitor operation.
list_predictor_backtest_export_jobs	Returns a list of predictor backtest export jobs created using the CreatePredictorBacktestExport operation.
list_predictors	Returns a list of predictors created using the CreateAutoPredictor or CreatePredictor operations.
list_tags_for_resource	Lists the tags for an Amazon Forecast resource.
list_what_if_analyses	Returns a list of what-if analyses created using the CreateWhatIfAnalysis operation.
list_what_if_forecast_exports	Returns a list of what-if forecast exports created using the CreateWhatIfForecastExport operation.
list_what_if_forecasts	Returns a list of what-if forecasts created using the CreateWhatIfForecast operation.
resume_resource	Resumes a stopped monitor resource.
stop_resource	Stops a resource.
tag_resource	Associates the specified tags to a resource with the specified resourceArn.
untag_resource	Deletes the specified tags from a resource.
update_dataset_group	Replaces the datasets in a dataset group with the specified datasets.

Examples

```
## Not run:
svc <- forecastservice()
svc$create_auto_predictor(
  Foo = 123
)

## End(Not run)
```

Description

This is the Amazon Fraud Detector API Reference. This guide is for developers who need detailed information about Amazon Fraud Detector API actions, data types, and errors. For more information about Amazon Fraud Detector features, see the [Amazon Fraud Detector User Guide](#).

We provide the Query API as well as AWS software development kits (SDK) for Amazon Fraud Detector in Java and Python programming languages.

The Amazon Fraud Detector Query API provides HTTPS requests that use the HTTP verb GET or POST and a Query parameter Action. AWS SDK provides libraries, sample code, tutorials, and other resources for software developers who prefer to build applications using language-specific APIs instead of submitting a request over HTTP or HTTPS. These libraries provide basic functions that automatically take care of tasks such as cryptographically signing your requests, retrying requests, and handling error responses, so that it is easier for you to get started. For more information about the AWS SDKs, go to [Tools to build on AWS](#) page, scroll down to the **SDK** section, and choose plus (+) sign to expand the section.

Usage

```
frauddetector(  
    config = list(),  
    credentials = list(),  
    endpoint = NULL,  
    region = NULL  
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none">• credentials:<ul style="list-style-type: none">– creds:<ul style="list-style-type: none">* access_key_id: AWS access key ID* secret_access_key: AWS secret access key* session_token: AWS temporary session token– profile: The name of a profile to use. If not given, then the default profile is used.– anonymous: Set anonymous credentials.• endpoint: The complete URL to use for the constructed client.• region: The AWS Region used in instantiating the client.• close_connection: Immediately close all HTTP connections.• timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.• s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. http://s3.amazonaws.com/BUCKET/KEY.• stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none">• creds:<ul style="list-style-type: none">– access_key_id: AWS access key ID– secret_access_key: AWS secret access key

- **session_token**: AWS temporary session token
- **profile**: The name of a profile to use. If not given, then the default profile is used.
- **anonymous**: Set anonymous credentials.

endpoint Optional shorthand for complete URL to use for the constructed client.

region Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- frauddetector(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

batch_create_variable	Creates a batch of variables
batch_get_variable	Gets a batch of variables
cancel_batch_import_job	Cancels an in-progress batch import job
cancel_batch_prediction_job	Cancels the specified batch prediction job
create_batch_import_job	Creates a batch import job
create_batch_prediction_job	Creates a batch prediction job
create_detector_version	Creates a detector version
create_list	Creates a list
create_model	Creates a model using the specified model type
create_model_version	Creates a version of the model using the specified model type and model id
create_rule	Creates a rule for use with the specified detector
create_variable	Creates a variable
delete_batch_import_job	Deletes the specified batch import job ID record
delete_batch_prediction_job	Deletes a batch prediction job
delete_detector	Deletes the detector
delete_detector_version	Deletes the detector version
delete_entity_type	Deletes an entity type
delete_event	Deletes the specified event
delete_events_by_event_type	Deletes all events of a particular event type
delete_event_type	Deletes an event type
delete_external_model	Removes a SageMaker model from Amazon Fraud Detector
delete_label	Deletes a label
delete_list	Deletes the list, provided it is not used in a rule
delete_model	Deletes a model
delete_model_version	Deletes a model version
delete_outcome	Deletes an outcome
delete_rule	Deletes the rule
delete_variable	Deletes a variable
describe_detector	Gets all versions for a specified detector
describe_model_versions	Gets all of the model versions for the specified model type or for the specified mod
get_batch_import_jobs	Gets all batch import jobs or a specific job of the specified ID
get_batch_prediction_jobs	Gets all batch prediction jobs or a specific job if you specify a job ID
get_delete_events_by_event_type_status	Retrieves the status of a DeleteEventsByEventType action
get_detectors	Gets all detectors or a single detector if a detectorId is specified
get_detector_version	Gets a particular detector version
get_entity_types	Gets all entity types or a specific entity type if a name is specified
get_event	Retrieves details of events stored with Amazon Fraud Detector
get_event_prediction	Evaluates an event against a detector version
get_event_prediction_metadata	Gets details of the past fraud predictions for the specified event ID, event type, dete
get_event_types	Gets all event types or a specific event type if name is provided
get_external_models	Gets the details for one or more Amazon SageMaker models that have been import
get_kms_encryption_key	Gets the encryption key if a KMS key has been specified to be used to encrypt cont
get_labels	Gets all labels or a specific label if name is provided
get_list_elements	Gets all the elements in the specified list
get_lists_metadata	Gets the metadata of either all the lists under the account or the specified list
get_models	Gets one or more models
get_model_version	Gets the details of the specified model version
get_outcomes	Gets one or more outcomes

get_rules	Get all rules for a detector (paginated) if ruleId and ruleVersion are not specified
get_variables	Gets all of the variables or the specific variable
list_event_predictions	Gets a list of past predictions
list_tags_for_resource	Lists all tags associated with the resource
put_detector	Creates or updates a detector
put_entity_type	Creates or updates an entity type
put_event_type	Creates or updates an event type
put_external_model	Creates or updates an Amazon SageMaker model endpoint
put_kms_encryption_key	Specifies the KMS key to be used to encrypt content in Amazon Fraud Detector
put_label	Creates or updates label
put_outcome	Creates or updates an outcome
send_event	Stores events in Amazon Fraud Detector without generating fraud predictions for them
tag_resource	Assigns tags to a resource
untag_resource	Removes tags from a resource
update_detector_version	Updates a detector version
update_detector_version_metadata	Updates the detector version's description
update_detector_version_status	Updates the detector version's status
update_event_label	Updates the specified event with a new label
update_list	Updates a list
update_model	Updates model description
update_model_version	Updates a model version
update_model_version_status	Updates the status of a model version
update_rule_metadata	Updates a rule's metadata
update_rule_version	Updates a rule version resulting in a new rule version
update_variable	Updates a variable

Examples

```
## Not run:
svc <- frauddetector()
svc$batch_create_variable(
  Foo = 123
)
## End(Not run)
```

Description

Amazon Lex Build-Time Actions

Amazon Lex is an AWS service for building conversational voice and text interfaces. Use these actions to create, update, and delete conversational bots for new and existing client applications.

Usage

```
lexmodelbuildingservice(
    config = list(),
    credentials = list(),
    endpoint = NULL,
    region = NULL
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region.
	<ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter
	<ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```

svc <- lexmodelbuildingservice(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)

```

Operations

create_bot_version	Creates a new version of the bot based on the \$LATEST version
create_intent_version	Creates a new version of an intent based on the \$LATEST version of the intent
create_slot_type_version	Creates a new version of a slot type based on the \$LATEST version of the specified slot type
delete_bot	Deletes all versions of the bot, including the \$LATEST version
delete_bot_alias	Deletes an alias for the specified bot
delete_bot_channel_association	Deletes the association between an Amazon Lex bot and a messaging platform
delete_bot_version	Deletes a specific version of a bot
delete_intent	Deletes all versions of the intent, including the \$LATEST version
delete_intent_version	Deletes a specific version of an intent
delete_slot_type	Deletes all versions of the slot type, including the \$LATEST version
delete_slot_type_version	Deletes a specific version of a slot type
delete_utterances	Deletes stored utterances
get_bot	Returns metadata information for a specific bot
get_bot_alias	Returns information about an Amazon Lex bot alias

get_bot_aliases	Returns a list of aliases for a specified Amazon Lex bot
get_bot_channel_association	Returns information about the association between an Amazon Lex bot and a messaging platform
get_bot_channel_associations	Returns a list of all of the channels associated with the specified bot
get_bots	Returns bot information as follows:
get_bot_versions	Gets information about all of the versions of a bot
get_builtin_intent	Returns information about a built-in intent
get_builtin_intents	Gets a list of built-in intents that meet the specified criteria
get_builtin_slot_types	Gets a list of built-in slot types that meet the specified criteria
get_export	Exports the contents of a Amazon Lex resource in a specified format
get_import	Gets information about an import job started with the StartImport operation
get_intent	Returns information about an intent
get_intents	Returns intent information as follows:
get_intent_versions	Gets information about all of the versions of an intent
get_migration	Provides details about an ongoing or complete migration from an Amazon Lex V1 bot to an Amazon Lex V2 bot
get_migrations	Gets a list of migrations between Amazon Lex V1 and Amazon Lex V2
get_slot_type	Returns information about a specific version of a slot type
get_slot_types	Returns slot type information as follows:
get_slot_type_versions	Gets information about all versions of a slot type
get_utterances_view	Use the GetUtterancesView operation to get information about the utterances that your user has used to interact with your bot
list_tags_for_resource	Gets a list of tags associated with the specified resource
put_bot	Creates an Amazon Lex conversational bot or replaces an existing bot
put_bot_alias	Creates an alias for the specified version of the bot or replaces an alias for the specified bot
put_intent	Creates an intent or replaces an existing intent
put_slot_type	Creates a custom slot type or replaces an existing custom slot type
start_import	Starts a job to import a resource to Amazon Lex
start_migration	Starts migrating a bot from Amazon Lex V1 to Amazon Lex V2
tag_resource	Adds the specified tags to the specified resource
untag_resource	Removes tags from a bot, bot alias or bot channel

Examples

```
## Not run:
svc <- lexmodelbuildingservice()
# This example shows how to get configuration information for a bot.
svc$get_bot(
  name = "DocOrderPizza",
  versionOrAlias = "$LATEST"
)
## End(Not run)
```

Description

Amazon Lex Model Building V2

Usage

```
lexmodelsv2(
    config = list(),
    credentials = list(),
    endpoint = NULL,
    region = NULL
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region.
	<ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized.html
credentials	Optional credentials shorthand for the config parameter
	<ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- lexmodelsv2(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

<code>batch_create_custom_vocabulary_item</code>	Create a batch of custom vocabulary items for a given bot locale's custom vocabulary
<code>batch_delete_custom_vocabulary_item</code>	Delete a batch of custom vocabulary items for a given bot locale's custom vocabulary
<code>batch_update_custom_vocabulary_item</code>	Update a batch of custom vocabulary items for a given bot locale's custom vocabulary
<code>build_bot_locale</code>	Builds a bot, its intents, and its slot types into a specific locale
<code>create_bot</code>	Creates an Amazon Lex conversational bot
<code>create_bot_alias</code>	Creates an alias for the specified version of a bot
<code>create_bot_locale</code>	Creates a locale in the bot
<code>create_bot_replica</code>	Action to create a replication of the source bot in the secondary region

<code>create_bot_version</code>	Creates an immutable version of the bot
<code>create_export</code>	Creates a zip archive containing the contents of a bot or a bot locale
<code>create_intent</code>	Creates an intent
<code>create_resource_policy</code>	Creates a new resource policy with the specified policy statements
<code>create_resource_policy_statement</code>	Adds a new resource policy statement to a bot or bot alias
<code>create_slot</code>	Creates a slot in an intent
<code>create_slot_type</code>	Creates a custom slot type
<code>create_test_set_discrepancy_report</code>	Create a report that describes the differences between the bot and the test set
<code>create_upload_url</code>	Gets a pre-signed S3 write URL that you use to upload the zip archive when import
<code>delete_bot</code>	Deletes all versions of a bot, including the Draft version
<code>delete_bot_alias</code>	Deletes the specified bot alias
<code>delete_bot_locale</code>	Removes a locale from a bot
<code>delete_bot_replica</code>	The action to delete the replicated bot in the secondary region
<code>delete_bot_version</code>	Deletes a specific version of a bot
<code>delete_custom_vocabulary</code>	Removes a custom vocabulary from the specified locale in the specified bot
<code>delete_export</code>	Removes a previous export and the associated files stored in an S3 bucket
<code>delete_import</code>	Removes a previous import and the associated file stored in an S3 bucket
<code>delete_intent</code>	Removes the specified intent
<code>delete_resource_policy</code>	Removes an existing policy from a bot or bot alias
<code>delete_resource_policy_statement</code>	Deletes a policy statement from a resource policy
<code>delete_slot</code>	Deletes the specified slot from an intent
<code>delete_slot_type</code>	Deletes a slot type from a bot locale
<code>delete_test_set</code>	The action to delete the selected test set
<code>delete_utterances</code>	Deletes stored utterances
<code>describe_bot</code>	Provides metadata information about a bot
<code>describe_bot_alias</code>	Get information about a specific bot alias
<code>describe_bot_locale</code>	Describes the settings that a bot has for a specific locale
<code>describe_bot_recommendation</code>	Provides metadata information about a bot recommendation
<code>describe_bot_replica</code>	Monitors the bot replication status through the UI console
<code>describe_bot_resource_generation</code>	Returns information about a request to generate a bot through natural language desc
<code>describe_bot_version</code>	Provides metadata about a version of a bot
<code>describe_custom_vocabulary_metadata</code>	Provides metadata information about a custom vocabulary
<code>describe_export</code>	Gets information about a specific export
<code>describe_import</code>	Gets information about a specific import
<code>describe_intent</code>	Returns metadata about an intent
<code>describe_resource_policy</code>	Gets the resource policy and policy revision for a bot or bot alias
<code>describe_slot</code>	Gets metadata information about a slot
<code>describe_slot_type</code>	Gets metadata information about a slot type
<code>describe_test_execution</code>	Gets metadata information about the test execution
<code>describe_test_set</code>	Gets metadata information about the test set
<code>describe_test_set_discrepancy_report</code>	Gets metadata information about the test set discrepancy report
<code>describe_test_set_generation</code>	Gets metadata information about the test set generation
<code>generate_bot_element</code>	Generates sample utterances for an intent
<code>get_test_execution_artifacts_url</code>	The pre-signed Amazon S3 URL to download the test execution result artifacts
<code>list_aggregated_utterances</code>	Provides a list of utterances that users have sent to the bot
<code>list_bot_aliases</code>	Gets a list of aliases for the specified bot
<code>list_bot_alias_replicas</code>	The action to list the replicated bots created from the source bot alias
<code>list_bot_locales</code>	Gets a list of locales for the specified bot

list_bot_recommendations	Get a list of bot recommendations that meet the specified criteria
list_bot_replicas	The action to list the replicated bots
list_bot_resource_generations	Lists the generation requests made for a bot locale
list_bots	Gets a list of available bots
list_bot_version_replicas	Contains information about all the versions replication statuses applicable for Global
list_bot_versions	Gets information about all of the versions of a bot
list_builtin_intents	Gets a list of built-in intents provided by Amazon Lex that you can use in your bot
list_builtin_slot_types	Gets a list of built-in slot types that meet the specified criteria
list_custom_vocabulary_items	Paginated list of custom vocabulary items for a given bot locale's custom vocabular
list_exports	Lists the exports for a bot, bot locale, or custom vocabulary
list_imports	Lists the imports for a bot, bot locale, or custom vocabulary
list_intent_metrics	Retrieves summary metrics for the intents in your bot
list_intent_paths	Retrieves summary statistics for a path of intents that users take over sessions with y
list_intents	Get a list of intents that meet the specified criteria
list_intent_stage_metrics	Retrieves summary metrics for the stages within intents in your bot
list_recommended_intents	Gets a list of recommended intents provided by the bot recommendation that you ca
list_session_analytics_data	Retrieves a list of metadata for individual user sessions with your bot
list_session_metrics	Retrieves summary metrics for the user sessions with your bot
list_slots	Gets a list of slots that match the specified criteria
list_slot_types	Gets a list of slot types that match the specified criteria
list_tags_for_resource	Gets a list of tags associated with a resource
list_test_execution_result_items	Gets a list of test execution result items
list_test_executions	The list of test set executions
list_test_set_records	The list of test set records
list_test_sets	The list of the test sets
list_utterance_analytics_data	To use this API operation, your IAM role must have permissions to perform the Lis
list_utterance_metrics	To use this API operation, your IAM role must have permissions to perform the Lis
search_associated_transcripts	Search for associated transcripts that meet the specified criteria
start_bot_recommendation	Use this to provide your transcript data, and to start the bot recommendation proces
start_bot_resource_generation	Starts a request for the descriptive bot builder to generate a bot locale configuration
start_import	Starts importing a bot, bot locale, or custom vocabulary from a zip archive that you
start_test_execution	The action to start test set execution
start_test_set_generation	The action to start the generation of test set
stop_bot_recommendation	Stop an already running Bot Recommendation request
tag_resource	Adds the specified tags to the specified resource
untag_resource	Removes tags from a bot, bot alias, or bot channel
update_bot	Updates the configuration of an existing bot
update_bot_alias	Updates the configuration of an existing bot alias
update_bot_locale	Updates the settings that a bot has for a specific locale
update_bot_recommendation	Updates an existing bot recommendation request
update_export	Updates the password used to protect an export zip archive
update_intent	Updates the settings for an intent
update_resource_policy	Replaces the existing resource policy for a bot or bot alias with a new one
update_slot	Updates the settings for a slot
update_slot_type	Updates the configuration of an existing slot type
update_test_set	The action to update the test set

Examples

```
## Not run:
svc <- lexmodelsrv2()
svc$batch_create_custom_vocabulary_item(
  Foo = 123
)
## End(Not run)
```

lexruntimeservice *Amazon Lex Runtime Service*

Description

Amazon Lex provides both build and runtime endpoints. Each endpoint provides a set of operations (API). Your conversational bot uses the runtime API to understand user utterances (user input text or voice). For example, suppose a user says "I want pizza", your bot sends this input to Amazon Lex using the runtime API. Amazon Lex recognizes that the user request is for the OrderPizza intent (one of the intents defined in the bot). Then Amazon Lex engages in user conversation on behalf of the bot to elicit required information (slot values, such as pizza size and crust type), and then performs fulfillment activity (that you configured when you created the bot). You use the build-time API to create and manage your Amazon Lex bot. For a list of build-time operations, see the build-time API, .

Usage

```
lexruntimeservice(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

- | | |
|---------------|---|
| config | Optional configuration of credentials, endpoint, and/or region. |
|---------------|---|
- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.
 - **anonymous:** Set anonymous credentials.
 - **endpoint:** The complete URL to use for the constructed client.

	<ul style="list-style-type: none"> • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- lexruntimeservice(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),

```

```

credentials = list(
  creds = list(
    access_key_id = "string",
    secret_access_key = "string",
    session_token = "string"
  ),
  profile = "string",
  anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

delete_session	Removes session information for a specified bot, alias, and user ID
get_session	Returns session information for a specified bot, alias, and user ID
post_content	Sends user input (text or speech) to Amazon Lex
post_text	Sends user input to Amazon Lex
put_session	Creates a new session or modifies an existing session with an Amazon Lex bot

Examples

```

## Not run:
svc <- lexruntimev2()
svc$delete_session(
  Foo = 123
)

## End(Not run)

```

Description

This section contains documentation for the Amazon Lex V2 Runtime V2 API operations.

Usage

```

lexruntimev2(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)

```

Arguments

config	Optional configuration of credentials, endpoint, and/or region.
	<ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized.html
credentials	Optional credentials shorthand for the config parameter
	<ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- lexruntimev2(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",

```

```

    secret_access_key = "string",
    session_token = "string"
),
profile = "string",
anonymous = "logical"
),
endpoint = "string",
region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
stsRegionalEndpoint = "string"
),
credentials = list(
  creds = list(
    accessKeyId = "string",
    secretAccessKey = "string",
    sessionToken = "string"
),
profile = "string",
anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

delete_session	Removes session information for a specified bot, alias, and user ID
get_session	Returns session information for a specified bot, alias, and user
put_session	Creates a new session or modifies an existing session with an Amazon Lex V2 bot
recognize_text	Sends user input to Amazon Lex V2
recognize_utterance	Sends user input to Amazon Lex V2

Examples

```

## Not run:
svc <- lexruntimev2()
svc$delete_session(
  Foo = 123
)

## End(Not run)

```

lookoutequipment	<i>Amazon Lookout for Equipment</i>
------------------	-------------------------------------

Description

Amazon Lookout for Equipment is a machine learning service that uses advanced analytics to identify anomalies in machines from sensor data for use in predictive maintenance.

Usage

```
lookoutequipment(  
    config = list(),  
    credentials = list(),  
    endpoint = NULL,  
    region = NULL  
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none">• credentials:<ul style="list-style-type: none">– creds:<ul style="list-style-type: none">* access_key_id: AWS access key ID* secret_access_key: AWS secret access key* session_token: AWS temporary session token– profile: The name of a profile to use. If not given, then the default profile is used.– anonymous: Set anonymous credentials.• endpoint: The complete URL to use for the constructed client.• region: The AWS Region used in instantiating the client.• close_connection: Immediately close all HTTP connections.• timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.• s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. http://s3.amazonaws.com/BUCKET/KEY.• stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-entities.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none">• creds:<ul style="list-style-type: none">– access_key_id: AWS access key ID– secret_access_key: AWS secret access key– session_token: AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.
- **anonymous:** Set anonymous credentials.

`endpoint` Optional shorthand for complete URL to use for the constructed client.
`region` Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- lookoutequipment(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

create_dataset	Creates a container for a collection of data being ingested for analysis
--------------------------------	--

<code>create_inference_scheduler</code>	Creates a scheduled inference
<code>create_label</code>	Creates a label for an event
<code>create_label_group</code>	Creates a group of labels
<code>create_model</code>	Creates a machine learning model for data inference
<code>create_retraining_scheduler</code>	Creates a retraining scheduler on the specified model
<code>delete_dataset</code>	Deletes a dataset and associated artifacts
<code>delete_inference_scheduler</code>	Deletes an inference scheduler that has been set up
<code>delete_label</code>	Deletes a label
<code>delete_label_group</code>	Deletes a group of labels
<code>delete_model</code>	Deletes a machine learning model currently available for Amazon Lookout for Equipment
<code>delete_resource_policy</code>	Deletes the resource policy attached to the resource
<code>delete_retraining_scheduler</code>	Deletes a retraining scheduler from a model
<code>describe_data_ingestion_job</code>	Provides information on a specific data ingestion job such as creation time, dataset ARN, and
<code>describe_dataset</code>	Provides a JSON description of the data in each time series dataset, including names, column
<code>describe_inference_scheduler</code>	Specifies information about the inference scheduler being used, including name, model, statu
<code>describe_label</code>	Returns the name of the label
<code>describe_label_group</code>	Returns information about the label group
<code>describe_model</code>	Provides a JSON containing the overall information about a specific machine learning model,
<code>describe_model_version</code>	Retrieves information about a specific machine learning model version
<code>describe_resource_policy</code>	Provides the details of a resource policy attached to a resource
<code>describe_retraining_scheduler</code>	Provides a description of the retraining scheduler, including information such as the model na
<code>import_dataset</code>	Imports a dataset
<code>import_model_version</code>	Imports a model that has been trained successfully
<code>list_data_ingestion_jobs</code>	Provides a list of all data ingestion jobs, including dataset name and ARN, S3 location of the
<code>list_datasets</code>	Lists all datasets currently available in your account, filtering on the dataset name
<code>list_inference_events</code>	Lists all inference events that have been found for the specified inference scheduler
<code>list_inference_executions</code>	Lists all inference executions that have been performed by the specified inference scheduler
<code>list_inference_schedulers</code>	Retrieves a list of all inference schedulers currently available for your account
<code>list_label_groups</code>	Returns a list of the label groups
<code>list_labels</code>	Provides a list of labels
<code>list_models</code>	Generates a list of all models in the account, including model name and ARN, dataset, and sta
<code>list_model_versions</code>	Generates a list of all model versions for a given model, including the model version, model v
<code>list_retrainingSchedulers</code>	Lists all retraining schedulers in your account, filtering by model name prefix and status
<code>list_sensor_statistics</code>	Lists statistics about the data collected for each of the sensors that have been successfully ing
<code>list_tags_for_resource</code>	Lists all the tags for a specified resource, including key and value
<code>put_resource_policy</code>	Creates a resource control policy for a given resource
<code>start_data_ingestion_job</code>	Starts a data ingestion job
<code>start_inference_scheduler</code>	Starts an inference scheduler
<code>start_retraining_scheduler</code>	Starts a retraining scheduler
<code>stop_inference_scheduler</code>	Stops an inference scheduler
<code>stop_retraining_scheduler</code>	Stops a retraining scheduler
<code>tag_resource</code>	Associates a given tag to a resource in your account
<code>untag_resource</code>	Removes a specific tag from a given resource
<code>update_active_model_version</code>	Sets the active model version for a given machine learning model
<code>update_inference_scheduler</code>	Updates an inference scheduler
<code>update_label_group</code>	Updates the label group
<code>update_model</code>	Updates a model in the account
<code>update_retraining_scheduler</code>	Updates a retraining scheduler

Examples

```
## Not run:
svc <- lookoutequipment()
#
svc$create_retraining_scheduler(
  ClientToken = "sample-client-token",
  LookbackWindow = "P360D",
  ModelName = "sample-model",
  PromoteMode = "MANUAL",
  RetrainingFrequency = "P1M"
)
## End(Not run)
```

lookoutmetrics *Amazon Lookout for Metrics*

Description

This is the *Amazon Lookout for Metrics API Reference*. For an introduction to the service with tutorials for getting started, visit [Amazon Lookout for Metrics Developer Guide](#).

Usage

```
lookoutmetrics(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

- | | |
|--------|--|
| config | Optional configuration of credentials, endpoint, and/or region. |
| | <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. |
| | <ul style="list-style-type: none"> • endpoint: The complete URL to use for the constructed client. |

	<ul style="list-style-type: none"> • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoints.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- lookoutmetrics(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
)
```

```

credentials = list(
    creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

activate_anomaly_detector	Activates an anomaly detector
back_test_anomaly_detector	Runs a backtest for anomaly detection for the specified resource
create_alert	Creates an alert for an anomaly detector
create_anomaly_detector	Creates an anomaly detector
create_metric_set	Creates a dataset
deactivate_anomaly_detector	Deactivates an anomaly detector
delete_alert	Deletes an alert
delete_anomaly_detector	Deletes a detector
describe_alert	Describes an alert
describe_anomaly_detection_executions	Returns information about the status of the specified anomaly detection jobs
describe_anomaly_detector	Describes a detector
describe_metric_set	Describes a dataset
detect_metric_set_config	Detects an Amazon S3 dataset's file format, interval, and offset
get_anomaly_group	Returns details about a group of anomalous metrics
get_data_quality_metrics	Returns details about the requested data quality metrics
get_feedback	Get feedback for an anomaly group
get_sample_data	Returns a selection of sample records from an Amazon S3 datasource
list_alerts	Lists the alerts attached to a detector
list_anomaly_detectors	Lists the detectors in the current AWS Region
list_anomaly_group_related_metrics	Returns a list of measures that are potential causes or effects of an anomaly group
list_anomaly_group_summaries	Returns a list of anomaly groups
list_anomaly_group_time_series	Gets a list of anomalous metrics for a measure in an anomaly group
list_metric_sets	Lists the datasets in the current AWS Region
list_tags_for_resource	Gets a list of tags for a detector, dataset, or alert
put_feedback	Add feedback for an anomalous metric
tag_resource	Adds tags to a detector, dataset, or alert
untag_resource	Removes tags from a detector, dataset, or alert
update_alert	Make changes to an existing alert
update_anomaly_detector	Updates a detector
update_metric_set	Updates a dataset

Examples

```
## Not run:  
svc <- lookoutmetrics()  
svc$activate_anomaly_detector(  
  Foo = 123  
)  
  
## End(Not run)
```

machinelearning *Amazon Machine Learning*

Description

Definition of the public APIs exposed by Amazon Machine Learning

Usage

```
machinelearning(  
  config = list(),  
  credentials = list(),  
  endpoint = NULL,  
  region = NULL  
)
```

Arguments

- | | |
|--------|--|
| config | Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none">• credentials:<ul style="list-style-type: none">– creds:<ul style="list-style-type: none">* access_key_id: AWS access key ID* secret_access_key: AWS secret access key* session_token: AWS temporary session token– profile: The name of a profile to use. If not given, then the default profile is used.– anonymous: Set anonymous credentials.• endpoint: The complete URL to use for the constructed client.• region: The AWS Region used in instantiating the client.• close_connection: Immediately close all HTTP connections.• timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.• s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. |
|--------|--|

	<ul style="list-style-type: none"> • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – accessKeyId: AWS access key ID – secretAccessKey: AWS secret access key – sessionToken: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- machinelearning(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
  )
)
```

```

    anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

<code>add_tags</code>	Adds one or more tags to an object, up to a limit of 10
<code>create_batch_prediction</code>	Generates predictions for a group of observations
<code>create_data_source_from_rds</code>	Creates a DataSource object from an Amazon Relational Database Service (Amazon RDS) database
<code>create_data_source_from_redshift</code>	Creates a DataSource from a database hosted on an Amazon Redshift cluster
<code>create_data_source_from_s3</code>	Creates a DataSource object
<code>create_evaluation</code>	Creates a new Evaluation of an MLModel
<code>create_ml_model</code>	Creates a new MLModel using the DataSource and the recipe as information sources
<code>create_realtime_endpoint</code>	Creates a real-time endpoint for the MLModel
<code>delete_batch_prediction</code>	Assigns the DELETED status to a BatchPrediction, rendering it unusable
<code>delete_data_source</code>	Assigns the DELETED status to a DataSource, rendering it unusable
<code>delete_evaluation</code>	Assigns the DELETED status to an Evaluation, rendering it unusable
<code>delete_ml_model</code>	Assigns the DELETED status to an MLModel, rendering it unusable
<code>delete_realtime_endpoint</code>	Deletes a real time endpoint of an MLModel
<code>delete_tags</code>	Deletes the specified tags associated with an ML object
<code>describe_batch_predictions</code>	Returns a list of BatchPrediction operations that match the search criteria in the request
<code>describe_data_sources</code>	Returns a list of DataSource that match the search criteria in the request
<code>describe_evaluations</code>	Returns a list of DescribeEvaluations that match the search criteria in the request
<code>describe_ml_models</code>	Returns a list of MLModel that match the search criteria in the request
<code>describe_tags</code>	Describes one or more of the tags for your Amazon ML object
<code>get_batch_prediction</code>	Returns a BatchPrediction that includes detailed metadata, status, and data file information
<code>get_data_source</code>	Returns a DataSource that includes metadata and data file information, as well as the current status
<code>get_evaluation</code>	Returns an Evaluation that includes metadata as well as the current status of the Evaluation
<code>get_ml_model</code>	Returns an MLModel that includes detailed metadata, data source information, and the current status
<code>predict</code>	Generates a prediction for the observation using the specified ML Model
<code>update_batch_prediction</code>	Updates the BatchPredictionName of a BatchPrediction
<code>update_data_source</code>	Updates the DataSourceName of a DataSource
<code>update_evaluation</code>	Updates the EvaluationName of an Evaluation
<code>update_ml_model</code>	Updates the MLModelName and the ScoreThreshold of an MLModel

Examples

```

## Not run:
svc <- machinelearning()
svc$add_tags(
  Foo = 123
)

## End(Not run)

```

panorama

AWS Panorama

Description

Overview

This is the *AWS Panorama API Reference*. For an introduction to the service, see [What is AWS Panorama?](#) in the *AWS Panorama Developer Guide*.

Usage

```
panorama(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none">• credentials:<ul style="list-style-type: none">– creds:<ul style="list-style-type: none">* access_key_id: AWS access key ID* secret_access_key: AWS secret access key* session_token: AWS temporary session token– profile: The name of a profile to use. If not given, then the default profile is used.– anonymous: Set anonymous credentials.• endpoint: The complete URL to use for the constructed client.• region: The AWS Region used in instantiating the client.• close_connection: Immediately close all HTTP connections.• timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.• s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>.• stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoints.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none">• creds:<ul style="list-style-type: none">– access_key_id: AWS access key ID– secret_access_key: AWS secret access key– session_token: AWS temporary session token• profile: The name of a profile to use. If not given, then the default profile is used.• anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- panorama(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

<code>create_application_instance</code>	Creates an application instance and deploys it to a device
<code>create_job_for_devices</code>	Creates a job to run on a device
<code>create_node_from_template_job</code>	Creates a camera stream node
<code>create_package</code>	Creates a package and storage location in an Amazon S3 access point
<code>create_package_import_job</code>	Imports a node package
<code>delete_device</code>	Deletes a device
<code>delete_package</code>	Deletes a package
<code>deregister_package_version</code>	Deregisters a package version

<code>describe_application_instance</code>	Returns information about an application instance on a device
<code>describe_application_instance_details</code>	Returns information about an application instance's configuration manifest
<code>describe_device</code>	Returns information about a device
<code>describe_device_job</code>	Returns information about a device job
<code>describe_node</code>	Returns information about a node
<code>describe_node_from_template_job</code>	Returns information about a job to create a camera stream node
<code>describe_package</code>	Returns information about a package
<code>describe_package_import_job</code>	Returns information about a package import job
<code>describe_package_version</code>	Returns information about a package version
<code>list_application_instance_dependencies</code>	Returns a list of application instance dependencies
<code>list_application_instance_node_instances</code>	Returns a list of application node instances
<code>list_application_instances</code>	Returns a list of application instances
<code>list_devices</code>	Returns a list of devices
<code>list_devices_jobs</code>	Returns a list of jobs
<code>list_node_from_template_jobs</code>	Returns a list of camera stream node jobs
<code>list_nodes</code>	Returns a list of nodes
<code>list_package_import_jobs</code>	Returns a list of package import jobs
<code>list_packages</code>	Returns a list of packages
<code>list_tags_for_resource</code>	Returns a list of tags for a resource
<code>provision_device</code>	Creates a device and returns a configuration archive
<code>register_package_version</code>	Registers a package version
<code>remove_application_instance</code>	Removes an application instance
<code>signal_application_instance_node_instances</code>	Signal camera nodes to stop or resume
<code>tag_resource</code>	Tags a resource
<code>untag_resource</code>	Removes tags from a resource
<code>update_device_metadata</code>	Updates a device's metadata

Examples

```
## Not run:
svc <- panorama()
svc$create_application_instance(
  Foo = 123
)

## End(Not run)
```

Description

Amazon Personalize is a machine learning service that makes it easy to add individualized recommendations to customers.

Usage

```
personalize(  
    config = list(),  
    credentials = list(),  
    endpoint = NULL,  
    region = NULL  
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none">• credentials:<ul style="list-style-type: none">– creds:<ul style="list-style-type: none">* access_key_id: AWS access key ID* secret_access_key: AWS secret access key* session_token: AWS temporary session token– profile: The name of a profile to use. If not given, then the default profile is used.– anonymous: Set anonymous credentials.• endpoint: The complete URL to use for the constructed client.• region: The AWS Region used in instantiating the client.• close_connection: Immediately close all HTTP connections.• timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.• s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>.• stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none">• creds:<ul style="list-style-type: none">– access_key_id: AWS access key ID– secret_access_key: AWS secret access key– session_token: AWS temporary session token• profile: The name of a profile to use. If not given, then the default profile is used.• anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- personalize(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

create_batch_inference_job	Generates batch recommendations based on a list of items or users stored in Amazon S3 and Amazon Redshift.
create_batch_segment_job	Creates a batch segment job
create_campaign	You incur campaign costs while it is active
create_dataset	Creates an empty dataset and adds it to the specified dataset group
create_dataset_export_job	Creates a job that exports data from your dataset to an Amazon S3 bucket
create_dataset_group	Creates an empty dataset group
create_dataset_import_job	Creates a job that imports training data from your data source (an Amazon S3 bucket) to an Amazon Personalize dataset.
create_event_tracker	Creates an event tracker that you use when adding event data to a specified dataset group using the <code>putEvents</code> operation.
create_filter	Creates a recommendation filter
create_metric_attribution	Creates a metric attribution
create_recommender	Creates a recommender with the recipe (a Domain dataset group use case) you specify
create_schema	Creates an Amazon Personalize schema from the specified schema string
create_solution	After you create a solution, you can't change its configuration
create_solution_version	Trains or retrains an active solution in a Custom dataset group

delete_campaign	Removes a campaign by deleting the solution deployment
delete_dataset	Deletes a dataset
delete_dataset_group	Deletes a dataset group
delete_event_tracker	Deletes the event tracker
delete_filter	Deletes a filter
delete_metric_attribution	Deletes a metric attribution
delete_recommender	Deactivates and removes a recommender
delete_schema	Deletes a schema
delete_solution	Deletes all versions of a solution and the Solution object itself
describe_algorithm	Describes the given algorithm
describe_batch_inference_job	Gets the properties of a batch inference job including name, Amazon Resource Name (ARN), and status.
describe_batch_segment_job	Gets the properties of a batch segment job including name, Amazon Resource Name (ARN), and status.
describe_campaign	Describes the given campaign, including its status
describe_dataset	Describes the given dataset
describe_dataset_export_job	Describes the dataset export job created by CreateDatasetExportJob, including the export job's ARN, status, and other properties.
describe_dataset_group	Describes the given dataset group
describe_dataset_import_job	Describes the dataset import job created by CreateDatasetImportJob, including the import job's ARN, status, and other properties.
describe_event_tracker	Describes an event tracker
describe_feature_transformation	Describes the given feature transformation
describe_filter	Describes a filter's properties
describe_metric_attribution	Describes a metric attribution
describe_recipe	Describes a recipe
describe_recommender	Describes the given recommender, including its status
describe_schema	Describes a schema
describe_solution	Describes a solution
describe_solution_version	Describes a specific version of a solution
get_solution_metrics	Gets the metrics for the specified solution version
list_batch_inference_jobs	Gets a list of the batch inference jobs that have been performed off of a solution version
list_batch_segment_jobs	Gets a list of the batch segment jobs that have been performed off of a solution version that use the given solution.
list_campaigns	Returns a list of campaigns that use the given solution
list_dataset_export_jobs	Returns a list of dataset export jobs that use the given dataset
list_dataset_groups	Returns a list of dataset groups
list_dataset_import_jobs	Returns a list of dataset import jobs that use the given dataset
list_datasets	Returns the list of datasets contained in the given dataset group
list_event_trackers	Returns the list of event trackers associated with the account
list_filters	Lists all filters that belong to a given dataset group
list_metric_attribution_metrics	Lists the metrics for the metric attribution
list_metric_attributions	Lists metric attributions
list_recipes	Returns a list of available recipes
list_recommenders	Returns a list of recommenders in a given Domain dataset group
list_schemas	Returns the list of schemas associated with the account
list_solutions	Returns a list of solutions in a given dataset group
list_solution_versions	Returns a list of solution versions for the given solution
list_tags_for_resource	Get a list of tags attached to a resource
start_recommender	Starts a recommender that is INACTIVE
stop_recommender	Stops a recommender that is ACTIVE
stop_solution_version_creation	Stops creating a solution version that is in a state of CREATE_PENDING or CREATE_IN_PROGRESS.
tag_resource	Add a list of tags to a resource

untag_resource	Removes the specified tags that are attached to a resource
update_campaign	Updates a campaign to deploy a retrained solution version with an existing campaign, change its configuration, or both.
update_dataset	Update a dataset to replace its schema with a new or existing one
update_metric_attribution	Updates a metric attribution
update_recommender	Updates the recommender to modify the recommender configuration

Examples

```
## Not run:
svc <- personalize()
svc$create_batch_inference_job(
  Foo = 123
)
## End(Not run)
```

personalizeevents *Amazon Personalize Events*

Description

Amazon Personalize can consume real-time user event data, such as *stream* or *click* data, and use it for model training either alone or combined with historical data. For more information see [Recording item interaction events](#).

Usage

```
personalizeevents(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

- | | |
|--------|---|
| config | Optional configuration of credentials, endpoint, and/or region. |
|--------|---|
- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.

	<ul style="list-style-type: none"> – anonymous: Set anonymous credentials.
	<ul style="list-style-type: none"> • endpoint: The complete URL to use for the constructed client.
	<ul style="list-style-type: none"> • region: The AWS Region used in instantiating the client.
	<ul style="list-style-type: none"> • close_connection: Immediately close all HTTP connections.
	<ul style="list-style-type: none"> • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.
	<ul style="list-style-type: none"> • s3_force_path_style: Set this to <code>true</code> to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>.
	<ul style="list-style-type: none"> • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
<code>credentials</code>	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
<code>endpoint</code>	Optional shorthand for complete URL to use for the constructed client.
<code>region</code>	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- personalizeevents(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
  )
)
```

```

    stsRegionalEndpoint = "string"
),
credentials = list(
  creds = list(
    accessKeyId = "string",
    secretAccessKey = "string",
    sessionToken = "string"
  ),
  profile = "string",
  anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

put_action_interactions	Records action interaction event data
put_actions	Adds one or more actions to an Actions dataset
put_events	Records item interaction event data
put_items	Adds one or more items to an Items dataset
put_users	Adds one or more users to a Users dataset

Examples

```

## Not run:
svc <- personalizeevents()
svc$put_action_interactions(
  Foo = 123
)

## End(Not run)

```

Description

Amazon Personalize Runtime

Usage

```
personalizeruntime(
  config = list(),
```

```

    credentials = list(),
    endpoint = NULL,
    region = NULL
)

```

Arguments

config	Optional configuration of credentials, endpoint, and/or region.
	<ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized.html
credentials	Optional credentials shorthand for the config parameter
	<ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- personalizeruntime(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

<code>get_action_recommendations</code>	Returns a list of recommended actions in sorted in descending order by prediction score
<code>get_personalized_ranking</code>	Re-ranks a list of recommended items for the given user
<code>get_recommendations</code>	Returns a list of recommended items

Examples

```
## Not run:
svc <- personalizeruntime()
svc$get_action_recommendations(
  Foo = 123
)
```

```
## End(Not run)
```

polly*Amazon Polly*

Description

Amazon Polly is a web service that makes it easy to synthesize speech from text.

The Amazon Polly service provides API operations for synthesizing high-quality speech from plain text and Speech Synthesis Markup Language (SSML), along with managing pronunciations lexicons that enable you to get the best results for your application domain.

Usage

```
polly(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

- | | |
|--------------------|---|
| config | Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none">• credentials:<ul style="list-style-type: none">– creds:<ul style="list-style-type: none">* access_key_id: AWS access key ID* secret_access_key: AWS secret access key* session_token: AWS temporary session token– profile: The name of a profile to use. If not given, then the default profile is used.– anonymous: Set anonymous credentials.• endpoint: The complete URL to use for the constructed client.• region: The AWS Region used in instantiating the client.• close_connection: Immediately close all HTTP connections.• timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.• s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. http://s3.amazonaws.com/BUCKET/KEY.• stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized.html |
| credentials | Optional credentials shorthand for the config parameter <ul style="list-style-type: none">• creds:<ul style="list-style-type: none">– access_key_id: AWS access key ID– secret_access_key: AWS secret access key– session_token: AWS temporary session token |

- **profile:** The name of a profile to use. If not given, then the default profile is used.
- **anonymous:** Set anonymous credentials.

endpoint Optional shorthand for complete URL to use for the constructed client.
region Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- polly(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

delete_lexicon	Deletes the specified pronunciation lexicon stored in an Amazon Web Services Region
--------------------------------	---

<code>describe.voices</code>	Returns the list of voices that are available for use when requesting speech synthesis
<code>get.lexicon</code>	Returns the content of the specified pronunciation lexicon stored in an Amazon Web Services Region
<code>get.speech.synthesis.task</code>	Retrieves a specific SpeechSynthesisTask object based on its TaskID
<code>list.lexicons</code>	Returns a list of pronunciation lexicons stored in an Amazon Web Services Region
<code>list.speech.synthesis.tasks</code>	Returns a list of SpeechSynthesisTask objects ordered by their creation date
<code>put.lexicon</code>	Stores a pronunciation lexicon in an Amazon Web Services Region
<code>start.speech.synthesis.task</code>	Allows the creation of an asynchronous synthesis task, by starting a new SpeechSynthesisTask
<code>synthesize.speech</code>	Synthesizes UTF-8 input, plain text or SSML, to a stream of bytes

Examples

```
## Not run:
svc <- polly()
# Deletes a specified pronunciation lexicon stored in an AWS Region.
svc$delete_lexicon(
  Name = "example"
)

## End(Not run)
```

Description

This is the API Reference for [Amazon Rekognition Image](#), [Amazon Rekognition Custom Labels](#), [Amazon Rekognition Stored Video](#), [Amazon Rekognition Streaming Video](#). It provides descriptions of actions, data types, common parameters, and common errors.

Amazon Rekognition Image

- [associate_faces](#)
- [compare_faces](#)
- [create_collection](#)
- [create_user](#)
- [delete_collection](#)
- [delete_faces](#)
- [delete_user](#)
- [describe_collection](#)
- [detect_faces](#)
- [detect_labels](#)
- [detect_moderation_labels](#)

- `detect_protective_equipment`
- `detect_text`
- `disassociate_faces`
- `get_celebrity_info`
- `get_media_analysis_job`
- `index_faces`
- `list_collections`
- `ListMediaAnalysisJob`
- `list_faces`
- `list_users`
- `recognize_celebrities`
- `search_faces`
- `search_faces_by_image`
- `search_users`
- `search_users_by_image`
- `start_media_analysis_job`

Amazon Rekognition Custom Labels

- `copy_project_version`
- `create_dataset`
- `create_project`
- `create_project_version`
- `delete_dataset`
- `delete_project`
- `delete_project_policy`
- `delete_project_version`
- `describe_dataset`
- `describe_projects`
- `describe_project_versions`
- `detect_custom_labels`
- `distribute_dataset_entries`
- `list_dataset_entries`
- `list_dataset_labels`
- `list_project_policies`
- `put_project_policy`
- `start_project_version`
- `stop_project_version`
- `update_dataset_entries`

Amazon Rekognition Video Stored Video

- `get_celebrity_recognition`
- `get_content_moderation`
- `get_face_detection`
- `get_face_search`
- `get_label_detection`
- `get_person_tracking`
- `get_segment_detection`
- `get_text_detection`
- `start_celebrity_recognition`
- `start_content_moderation`
- `start_face_detection`
- `start_face_search`
- `start_label_detection`
- `start_person_tracking`
- `start_segment_detection`
- `start_text_detection`

Amazon Rekognition Video Streaming Video

- `create_stream_processor`
- `delete_stream_processor`
- `describe_stream_processor`
- `list_stream_processors`
- `start_stream_processor`
- `stop_stream_processor`
- `update_stream_processor`

Usage

```
rekognition(  
    config = list(),  
    credentials = list(),  
    endpoint = NULL,  
    region = NULL  
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region.
	<ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized.html
credentials	Optional credentials shorthand for the config parameter
	<ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- rekognition(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
```

```

        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
stsRegionalEndpoint = "string"
),
credentials = list(
    creds = list(
        accessKeyId = "string",
        secretAccessKey = "string",
        sessionToken = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

<code>associate_faces</code>	Associates one or more faces with an existing UserID
<code>compare_faces</code>	Compares a face in the source input image with each of the 100 largest faces detected in the target input image.
<code>copy_project_version</code>	This operation applies only to Amazon Rekognition Custom Labels
<code>create_collection</code>	Creates a collection in an AWS Region
<code>create_dataset</code>	This operation applies only to Amazon Rekognition Custom Labels
<code>create_face_liveness_session</code>	This API operation initiates a Face Liveness session
<code>create_project</code>	Creates a new Amazon Rekognition project
<code>create_project_version</code>	Creates a new version of Amazon Rekognition project (like a Custom Labels model or a collection).
<code>create_stream_processor</code>	Creates an Amazon Rekognition stream processor that you can use to detect and recognize faces in video streams.
<code>create_user</code>	Creates a new User within a collection specified by CollectionId
<code>delete_collection</code>	Deletes the specified collection
<code>delete_dataset</code>	This operation applies only to Amazon Rekognition Custom Labels
<code>delete_faces</code>	Deletes faces from a collection
<code>delete_project</code>	Deletes a Amazon Rekognition project
<code>delete_project_policy</code>	This operation applies only to Amazon Rekognition Custom Labels
<code>delete_project_version</code>	Deletes a Rekognition project model or project version, like a Amazon Rekognition Custom Label's version.
<code>delete_stream_processor</code>	Deletes the stream processor identified by Name
<code>delete_user</code>	Deletes the specified UserID within the collection
<code>describe_collection</code>	Describes the specified collection
<code>describe_dataset</code>	This operation applies only to Amazon Rekognition Custom Labels

<code>describe_projects</code>	Gets information about your Rekognition projects
<code>describe_project_versions</code>	Lists and describes the versions of an Amazon Rekognition project
<code>describe_stream_processor</code>	Provides information about a stream processor created by CreateStreamProcessor
<code>detect_custom_labels</code>	This operation applies only to Amazon Rekognition Custom Labels
<code>detect_faces</code>	Detects faces within an image that is provided as input
<code>detect_labels</code>	Detects instances of real-world entities within an image (JPEG or PNG) provided as input
<code>detect_moderation_labels</code>	Detects unsafe content in a specified JPEG or PNG format image
<code>detect_protective_equipment</code>	Detects Personal Protective Equipment (PPE) worn by people detected in an image
<code>detect_text</code>	Detects text in the input image and converts it into machine-readable text
<code>disassociate_faces</code>	Removes the association between a Face supplied in an array of FaceIds and the User
<code>distribute_dataset_entries</code>	This operation applies only to Amazon Rekognition Custom Labels
<code>get_celebrity_info</code>	Gets the name and additional information about a celebrity based on their Amazon Reko
<code>get_celebrity_recognition</code>	Gets the celebrity recognition results for a Amazon Rekognition Video analysis started by
<code>get_content_moderation</code>	Gets the inappropriate, unwanted, or offensive content analysis results for a Amazon Reko
<code>get_face_detection</code>	Gets face detection results for a Amazon Rekognition Video analysis started by StartFace
<code>get_face_liveness_session_results</code>	Retrieves the results of a specific Face Liveness session
<code>get_face_search</code>	Gets the face search results for Amazon Rekognition Video face search started by StartFa
<code>get_label_detection</code>	Gets the label detection results of a Amazon Rekognition Video analysis started by StartL
<code>get_media_analysis_job</code>	Retrieves the results for a given media analysis job
<code>get_person_tracking</code>	Gets the path tracking results of a Amazon Rekognition Video analysis started by StartPe
<code>get_segment_detection</code>	Gets the segment detection results of a Amazon Rekognition Video analysis started by Sta
<code>get_text_detection</code>	Gets the text detection results of a Amazon Rekognition Video analysis started by StartTe
<code>index_faces</code>	Detects faces in the input image and adds them to the specified collection
<code>list_collections</code>	Returns list of collection IDs in your account
<code>list_dataset_entries</code>	This operation applies only to Amazon Rekognition Custom Labels
<code>list_dataset_labels</code>	This operation applies only to Amazon Rekognition Custom Labels
<code>list_faces</code>	Returns metadata for faces in the specified collection
<code>list_media_analysis_jobs</code>	Returns a list of media analysis jobs
<code>list_project_policies</code>	This operation applies only to Amazon Rekognition Custom Labels
<code>list_stream_processors</code>	Gets a list of stream processors that you have created with CreateStreamProcessor
<code>list_tags_for_resource</code>	Returns a list of tags in an Amazon Rekognition collection, stream processor, or Custom L
<code>list_users</code>	Returns metadata of the User such as UserID in the specified collection
<code>put_project_policy</code>	This operation applies only to Amazon Rekognition Custom Labels
<code>recognize_celebrities</code>	Returns an array of celebrities recognized in the input image
<code>search_faces</code>	For a given input face ID, searches for matching faces in the collection the face belongs to
<code>search_faces_by_image</code>	For a given input image, first detects the largest face in the image, and then searches the s
<code>search_users</code>	Searches for UserIDs within a collection based on a FaceId or UserId
<code>search_users_by_image</code>	Searches for UserIDs using a supplied image
<code>start_celebrity_recognition</code>	Starts asynchronous recognition of celebrities in a stored video
<code>start_content_moderation</code>	Starts asynchronous detection of inappropriate, unwanted, or offensive content in a stored
<code>start_face_detection</code>	Starts asynchronous detection of faces in a stored video
<code>start_face_search</code>	Starts the asynchronous search for faces in a collection that match the faces of persons de
<code>start_label_detection</code>	Starts asynchronous detection of labels in a stored video
<code>start_media_analysis_job</code>	Initiates a new media analysis job
<code>start_person_tracking</code>	Starts the asynchronous tracking of a person's path in a stored video
<code>start_project_version</code>	This operation applies only to Amazon Rekognition Custom Labels
<code>start_segment_detection</code>	Starts asynchronous detection of segment detection in a stored video
<code>start_stream_processor</code>	Starts processing a stream processor

<code>start_text_detection</code>	Starts asynchronous detection of text in a stored video
<code>stop_project_version</code>	This operation applies only to Amazon Rekognition Custom Labels
<code>stop_stream_processor</code>	Stops a running stream processor that was created by CreateStreamProcessor
<code>tag_resource</code>	Adds one or more key-value tags to an Amazon Rekognition collection, stream processor, or project.
<code>untag_resource</code>	Removes one or more tags from an Amazon Rekognition collection, stream processor, or project.
<code>update_dataset_entries</code>	This operation applies only to Amazon Rekognition Custom Labels
<code>update_stream_processor</code>	Allows you to update a stream processor

Examples

```
## Not run:
svc <- rekognition()
# This operation associates one or more faces with an existing UserID.
svc$associate_faces(
  ClientRequestToken = "550e8400-e29b-41d4-a716-446655440002",
  CollectionId = "MyCollection",
  FaceIds = list(
    "f5817d37-94f6-4335-bfee-6cf79a3d806e",
    "851cb847-dccc-4fea-9309-9f4805967855",
    "35ebbb41-7f67-4263-908d-dd0ecba05ab9"
  ),
  UserId = "DemoUser",
  UserMatchThreshold = 70L
)
## End(Not run)
```

Description

Provides APIs for creating and managing SageMaker resources.

Other Resources:

- [SageMaker Developer Guide](#)
- [Amazon Augmented AI Runtime API Reference](#)

Usage

```
sagemaker(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region.
	<ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized.html
credentials	Optional credentials shorthand for the config parameter
	<ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- sagemaker(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",

```

```

        secret_access_key = "string",
        session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
stsRegionalEndpoint = "string"
),
credentials = list(
    creds = list(
        accessKeyId = "string",
        secretAccessKey = "string",
        sessionToken = "string"
    ),
    profile = "string",
    anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

add_association	Creates an association between the source and the destination
add_tags	Adds or overwrites one or more tags for the specified SageMaker resource
associate_trial_component	Associates a trial component with a trial
batch_describe_model_package	This action batch describes a list of versioned model packages
create_action	Creates an action
create_algorithm	Create a machine learning algorithm that you can use in SageMaker and Amazon
create_app	Creates a running app for the specified UserProfile
create_app_image_config	Creates a configuration for running a SageMaker image as a KernelGateway
create_artifact	Creates an artifact
create_auto_ml_job	Creates an Autopilot job also referred to as Autopilot experiment or AutoML job
create_auto_ml_job_v2	Creates an Autopilot job also referred to as Autopilot experiment or AutoML job
create_cluster	Creates a SageMaker HyperPod cluster
create_code_repository	Creates a Git repository as a resource in your SageMaker account
create_compilation_job	Starts a model compilation job
create_context	Creates a context
create_data_quality_job_definition	Creates a definition for a job that monitors data quality and drift
create_device_fleet	Creates a device fleet
create_domain	Creates a Domain
create_edge_deployment_plan	Creates an edge deployment plan, consisting of multiple stages
create_edge_deployment_stage	Creates a new stage in an existing edge deployment plan

<code>create_edge_packaging_job</code>	Starts a SageMaker Edge Manager model packaging job
<code>create_endpoint</code>	Creates an endpoint using the endpoint configuration specified in the request.
<code>create_endpoint_config</code>	Creates an endpoint configuration that SageMaker hosting services uses to host your endpoint.
<code>create_experiment</code>	Creates a SageMaker experiment
<code>create_feature_group</code>	Create a new FeatureGroup
<code>create_flow_definition</code>	Creates a flow definition
<code>create_hub</code>	Create a hub
<code>create_human_task_ui</code>	Defines the settings you will use for the human review workflow user interface.
<code>create_hyper_parameter_tuning_job</code>	Starts a hyperparameter tuning job
<code>create_image</code>	Creates a custom SageMaker image
<code>create_image_version</code>	Creates a version of the SageMaker image specified by ImageName
<code>create_inference_component</code>	Creates an inference component, which is a SageMaker hosting object type.
<code>create_inference_experiment</code>	Creates an inference experiment using the configurations specified in the request.
<code>create_inference_recommendations_job</code>	Starts a recommendation job
<code>create_labeling_job</code>	Creates a job that uses workers to label the data objects in your input data.
<code>create_model</code>	Creates a model in SageMaker
<code>create_model_bias_job_definition</code>	Creates the definition for a model bias job
<code>create_model_card</code>	Creates an Amazon SageMaker Model Card
<code>create_model_card_export_job</code>	Creates an Amazon SageMaker Model Card export job
<code>create_model_explainability_job_definition</code>	Creates the definition for a model explainability job
<code>create_model_package</code>	Creates a model package that you can use to create SageMaker models.
<code>create_model_package_group</code>	Creates a model group
<code>create_model_quality_job_definition</code>	Creates a definition for a job that monitors model quality and drift
<code>create_monitoring_schedule</code>	Creates a schedule that regularly starts Amazon SageMaker Processing jobs.
<code>create_notebook_instance</code>	Creates an SageMaker notebook instance
<code>create_notebook_instance_lifecycle_config</code>	Creates a lifecycle configuration that you can associate with a notebook instance.
<code>create_pipeline</code>	Creates a pipeline using a JSON pipeline definition
<code>create_presigned_domain_url</code>	Creates a URL for a specified UserProfile in a Domain
<code>create_presigned_notebook_instance_url</code>	Returns a URL that you can use to connect to the Jupyter server from a browser.
<code>create_processing_job</code>	Creates a processing job
<code>create_project</code>	Creates a machine learning (ML) project that can contain one or more training jobs.
<code>create_space</code>	Creates a space used for real time collaboration in a domain
<code>create_studio_lifecycle_config</code>	Creates a new Amazon SageMaker Studio Lifecycle Configuration
<code>create_training_job</code>	Starts a model training job
<code>create_transform_job</code>	Starts a transform job
<code>create_trial</code>	Creates an SageMaker trial
<code>create_trial_component</code>	Creates a trial component, which is a stage of a machine learning trial
<code>create_user_profile</code>	Creates a user profile
<code>create_workforce</code>	Use this operation to create a workforce
<code>create_workteam</code>	Creates a new work team for labeling your data
<code>delete_action</code>	Deletes an action
<code>delete_algorithm</code>	Removes the specified algorithm from your account
<code>delete_app</code>	Used to stop and delete an app
<code>delete_app_image_config</code>	Deletes an AppImageConfig
<code>delete_artifact</code>	Deletes an artifact
<code>delete_association</code>	Deletes an association
<code>delete_cluster</code>	Delete a SageMaker HyperPod cluster
<code>delete_code_repository</code>	Deletes the specified Git repository from your account

delete_compilation_job	Deletes the specified compilation job
delete_context	Deletes an context
delete_data_quality_job_definition	Deletes a data quality monitoring job definition
delete_device_fleet	Deletes a fleet
delete_domain	Used to delete a domain
delete_edge_deployment_plan	Deletes an edge deployment plan if (and only if) all the stages in the plan
delete_edge_deployment_stage	Delete a stage in an edge deployment plan if (and only if) the stage is in
delete_endpoint	Deletes an endpoint
delete_endpoint_config	Deletes an endpoint configuration
delete_experiment	Deletes an SageMaker experiment
delete_feature_group	Delete the FeatureGroup and any data that was written to the OnlineSto
delete_flow_definition	Deletes the specified flow definition
delete_hub	Delete a hub
delete_hub_content	Delete the contents of a hub
delete_human_task_ui	Use this operation to delete a human task user interface (worker task ter
delete_hyper_parameter_tuning_job	Deletes a hyperparameter tuning job
delete_image	Deletes a SageMaker image and all versions of the image
delete_image_version	Deletes a version of a SageMaker image
delete_inference_component	Deletes an inference component
delete_inference_experiment	Deletes an inference experiment
delete_model	Deletes a model
delete_model_bias_job_definition	Deletes an Amazon SageMaker model bias job definition
delete_model_card	Deletes an Amazon SageMaker Model Card
delete_model_explainability_job_definition	Deletes an Amazon SageMaker model explainability job definition
delete_model_package	Deletes a model package
delete_model_package_group	Deletes the specified model group
delete_model_package_group_policy	Deletes a model group resource policy
delete_model_quality_job_definition	Deletes the secified model quality monitoring job definition
delete_monitoring_schedule	Deletes a monitoring schedule
delete_notebook_instance	Deletes an SageMaker notebook instance
delete_notebook_instance_lifecycle_config	Deletes a notebook instance lifecycle configuration
delete_pipeline	Deletes a pipeline if there are no running instances of the pipeline
delete_project	Delete the specified project
delete_space	Used to delete a space
delete_studio_lifecycle_config	Deletes the Amazon SageMaker Studio Lifecycle Configuration
delete_tags	Deletes the specified tags from an SageMaker resource
delete_trial	Deletes the specified trial
delete_trial_component	Deletes the specified trial component
delete_user_profile	Deletes a user profile
delete_workforce	Use this operation to delete a workforce
delete_workteam	Deletes an existing work team
deregister_devices	Deregisters the specified devices
describe_action	Describes an action
describe_algorithm	Returns a description of the specified algorithm that is in your account
describe_app	Describes the app
describe_app_image_config	Describes an AppImageConfig
describe_artifact	Describes an artifact
describe_auto_ml_job	Returns information about an AutoML job created by calling CreateAu

<code>describe_auto_ml_job_v2</code>	Returns information about an AutoML job created by calling CreateAutoMLJob.
<code>describe_cluster</code>	Retrieves information of a SageMaker HyperPod cluster.
<code>describe_cluster_node</code>	Retrieves information of an instance (also called a node) interchangeably.
<code>describe_code_repository</code>	Gets details about the specified Git repository.
<code>describe_compilation_job</code>	Returns information about a model compilation job.
<code>describe_context</code>	Describes a context.
<code>describe_data_quality_job_definition</code>	Gets the details of a data quality monitoring job definition.
<code>describe_device</code>	Describes the device.
<code>describe_device_fleet</code>	A description of the fleet the device belongs to.
<code>describe_domain</code>	The description of the domain.
<code>describe_edge_deployment_plan</code>	Describes an edge deployment plan with deployment status per stage.
<code>describe_edge_packaging_job</code>	A description of edge packaging jobs.
<code>describe_endpoint</code>	Returns the description of an endpoint.
<code>describe_endpoint_config</code>	Returns the description of an endpoint configuration created using the CreateEndpointConfig API.
<code>describe_experiment</code>	Provides a list of an experiment's properties.
<code>describe_feature_group</code>	Use this operation to describe a FeatureGroup.
<code>describe_feature_metadata</code>	Shows the metadata for a feature within a feature group.
<code>describe_flow_definition</code>	Returns information about the specified flow definition.
<code>describe_hub</code>	Describe a hub.
<code>describe_hub_content</code>	Describe the content of a hub.
<code>describe_human_task_ui</code>	Returns information about the requested human task user interface (worker interface).
<code>describe_hyper_parameter_tuning_job</code>	Returns a description of a hyperparameter tuning job, depending on the request.
<code>describe_image</code>	Describes a SageMaker image.
<code>describe_image_version</code>	Describes a version of a SageMaker image.
<code>describe_inference_component</code>	Returns information about an inference component.
<code>describe_inference_experiment</code>	Returns details about an inference experiment.
<code>describe_inference_recommendations_job</code>	Provides the results of the Inference Recommender job.
<code>describe_labeling_job</code>	Gets information about a labeling job.
<code>describe_lineage_group</code>	Provides a list of properties for the requested lineage group.
<code>describe_model</code>	Describes a model that you created using the CreateModel API.
<code>describe_model_bias_job_definition</code>	Returns a description of a model bias job definition.
<code>describe_model_card</code>	Describes the content, creation time, and security configuration of an Amazon SageMaker Model Card.
<code>describe_model_card_export_job</code>	Describes an Amazon SageMaker Model Card export job.
<code>describe_model_explainability_job_definition</code>	Returns a description of a model explainability job definition.
<code>describe_model_package</code>	Returns a description of the specified model package, which is used to create a model.
<code>describe_model_package_group</code>	Gets a description for the specified model group.
<code>describe_model_quality_job_definition</code>	Returns a description of a model quality job definition.
<code>describe_monitoring_schedule</code>	Describes the schedule for a monitoring job.
<code>describe_notebook_instance</code>	Returns information about a notebook instance.
<code>describe_notebook_instance_lifecycle_config</code>	Returns a description of a notebook instance lifecycle configuration.
<code>describe_pipeline</code>	Describes the details of a pipeline.
<code>describe_pipeline_definition_for_execution</code>	Describes the details of an execution's pipeline definition.
<code>describe_pipeline_execution</code>	Describes the details of a pipeline execution.
<code>describe_processing_job</code>	Returns a description of a processing job.
<code>describe_project</code>	Describes the details of a project.
<code>describe_space</code>	Describes the space.
<code>describe_studio_lifecycle_config</code>	Describes the Amazon SageMaker Studio Lifecycle Configuration.
<code>describe_subscribed_workteam</code>	Gets information about a work team provided by a vendor.

describe_training_job	Returns information about a training job
describe_transform_job	Returns information about a transform job
describe_trial	Provides a list of a trial's properties
describe_trial_component	Provides a list of a trials component's properties
describe_user_profile	Describes a user profile
describe_workforce	Lists private workforce information, including workforce name, Amazon
describe_workteam	Gets information about a specific work team
disable_sagemaker_servicecatalog_portfolio	Disables using Service Catalog in SageMaker
disassociate_trial_component	Disassociates a trial component from a trial
enable_sagemaker_servicecatalog_portfolio	Enables using Service Catalog in SageMaker
get_device_fleet_report	Describes a fleet
get_lineage_group_policy	The resource policy for the lineage group
get_model_package_group_policy	Gets a resource policy that manages access for a model group
get_sagemaker_servicecatalog_portfolio_status	Gets the status of Service Catalog in SageMaker
get_scaling_configuration_recommendation	Starts an Amazon SageMaker Inference Recommender autoscaling reco
get_searchSuggestions	An auto-complete API for the search functionality in the SageMaker co
import_hub_content	Import hub content
list_actions	Lists the actions in your account and their properties
list_algorithms	Lists the machine learning algorithms that have been created
list_aliases	Lists the aliases of a specified image or image version
list_app_image_configs	Lists the AppImageConfigs in your account and their properties
list_apps	Lists apps
list_artifacts	Lists the artifacts in your account and their properties
list_associations	Lists the associations in your account and their properties
list_auto_ml_jobs	Request a list of jobs
list_candidates_for_auto_ml_job	List the candidates created for the job
list_cluster_nodes	Retrieves the list of instances (also called nodes interchangeably) in a S
list_clusters	Retrieves the list of SageMaker HyperPod clusters
list_code_repositories	Gets a list of the Git repositories in your account
list_compilation_jobs	Lists model compilation jobs that satisfy various filters
list_contexts	Lists the contexts in your account and their properties
list_data_quality_job_definitions	Lists the data quality job definitions in your account
list_device_fleets	Returns a list of devices in the fleet
list_devices	A list of devices
list_domains	Lists the domains
list_edge_deployment_plans	Lists all edge deployment plans
list_edge_packaging_jobs	Returns a list of edge packaging jobs
list_endpoint_configs	Lists endpoint configurations
list_endpoints	Lists endpoints
list_experiments	Lists all the experiments in your account
list_feature_groups	List FeatureGroups based on given filter and order
list_flow_definitions	Returns information about the flow definitions in your account
list_hub_contents	List the contents of a hub
list_hub_content_versions	List hub content versions
list_hubs	List all existing hubs
list_human_task_uis	Returns information about the human task user interfaces in your accou
list_hyper_parameter_tuning_jobs	Gets a list of HyperParameterTuningJobSummary objects that describe
list_images	Lists the images in your account and their properties

list_image_versions	Lists the versions of a specified image and their properties
list_inference_components	Lists the inference components in your account and their properties
list_inference_experiments	Returns the list of all inference experiments
list_inference_recommendations_jobs	Lists recommendation jobs that satisfy various filters
list_inference_recommendations_job_steps	Returns a list of the subtasks for an Inference Recommender job
list_labeling_jobs	Gets a list of labeling jobs
list_labeling_jobs_for_workteam	Gets a list of labeling jobs assigned to a specified work team
list_lineage_groups	A list of lineage groups shared with your Amazon Web Services account
list_model_bias_job_definitions	Lists model bias jobs definitions that satisfy various filters
list_model_card_export_jobs	List the export jobs for the Amazon SageMaker Model Card
list_model_cards	List existing model cards
list_model_card_versions	List existing versions of an Amazon SageMaker Model Card
list_model_explainability_job_definitions	Lists model explainability job definitions that satisfy various filters
list_model_metadata	Lists the domain, framework, task, and model name of standard machine learning models
list_model_package_groups	Gets a list of the model groups in your Amazon Web Services account
list_model_packages	Lists the model packages that have been created
list_model_quality_job_definitions	Gets a list of model quality monitoring job definitions in your account
list_models	Lists models created with the CreateModel API
list_monitoring_alert_history	Gets a list of past alerts in a model monitoring schedule
list_monitoring_alerts	Gets the alerts for a single monitoring schedule
list_monitoring_executions	Returns list of all monitoring job executions
list_monitoring_schedules	Returns list of all monitoring schedules
list_notebook_instance_lifecycle_configs	Lists notebook instance lifestyle configurations created with the CreateNotebookInstanceLifecycleConfig API
list_notebook_instances	Returns a list of the SageMaker notebook instances in the requester's account
list_pipeline_executions	Gets a list of the pipeline executions
list_pipeline_execution_steps	Gets a list of PipeLineExecutionStep objects
list_pipeline_parameters_for_execution	Gets a list of parameters for a pipeline execution
list_pipelines	Gets a list of pipelines
list_processing_jobs	Lists processing jobs that satisfy various filters
list_projects	Gets a list of the projects in an Amazon Web Services account
list_resource_catalogs	Lists Amazon SageMaker Catalogs based on given filters and orders
list_spaces	Lists spaces
list_stage_devices	Lists devices allocated to the stage, containing detailed device information
list_studio_lifecycle_configs	Lists the Amazon SageMaker Studio Lifecycle Configurations in your account
list_subscribed_workteams	Gets a list of the work teams that you are subscribed to in the Amazon VPC
list_tags	Returns the tags for the specified SageMaker resource
list_training_jobs	Lists training jobs
list_training_jobs_for_hyper_parameter_tuning_job	Gets a list of TrainingJobSummary objects that describe the training job
list_transform_jobs	Lists transform jobs
list_trial_components	Lists the trial components in your account
list_trials	Lists the trials in your account
list_user_profiles	Lists user profiles
list_workforces	Use this operation to list all private and vendor workforces in an Amazon VPC
list_workteams	Gets a list of private work teams that you have defined in a region
put_model_package_group_policy	Adds a resource policy to control access to a model group
query_lineage	Use this action to inspect your lineage and discover relationships between datasets
register_devices	Register devices
render_ui_template	Renders the UI template so that you can preview the worker's experience

retry_pipeline_execution	Retry the execution of the pipeline
search	Finds SageMaker resources that match a search query
send_pipeline_execution_step_failure	Notifies the pipeline that the execution of a callback step failed, along with the failure reason
send_pipeline_execution_step_success	Notifies the pipeline that the execution of a callback step succeeded and provides the result
start_edge_deployment_stage	Starts a stage in an edge deployment plan
start_inference_experiment	Starts an inference experiment
start_monitoring_schedule	Starts a previously stopped monitoring schedule
start_notebook_instance	Launches an ML compute instance with the latest version of the libraries and software components
start_pipeline_execution	Starts a pipeline execution
stop_auto_ml_job	A method for forcing a running job to shut down
stop_compilation_job	Stops a model compilation job
stop_edge_deployment_stage	Stops a stage in an edge deployment plan
stop_edge_packaging_job	Request to stop an edge packaging job
stop_hyper_parameter_tuning_job	Stops a running hyperparameter tuning job and all running training jobs
stop_inference_experiment	Stops an inference experiment
stop_inference_recommendations_job	Stops an Inference Recommender job
stop_labeling_job	Stops a running labeling job
stop_monitoring_schedule	Stops a previously started monitoring schedule
stop_notebook_instance	Terminates the ML compute instance
stop_pipeline_execution	Stops a pipeline execution
stop_processing_job	Stops a processing job
stop_training_job	Stops a training job
stop_transform_job	Stops a batch transform job
update_action	Updates an action
update_app_image_config	Updates the properties of an AppImageConfig
update_artifact	Updates an artifact
update_cluster	Updates a SageMaker HyperPod cluster
update_cluster_software	Updates the platform software of a SageMaker HyperPod cluster for security or performance
update_code_repository	Updates the specified Git repository with the specified values
update_context	Updates a context
update_device_fleet	Updates a fleet of devices
update_devices	Updates one or more devices in a fleet
update_domain	Updates the default settings for new user profiles in the domain
update_endpoint	Deploys the EndpointConfig specified in the request to a new fleet of instances
update_endpoint_weights_and_capacities	Updates variant weight of one or more variants associated with an existing endpoint
update_experiment	Adds, updates, or removes the description of an experiment
update_feature_group	Updates the feature group by either adding features or updating the online feature store
update_feature_metadata	Updates the description and parameters of the feature group
update_hub	Update a hub
update_image	Updates the properties of a SageMaker image
update_image_version	Updates the properties of a SageMaker image version
update_inference_component	Updates an inference component
update_inference_component_runtime_config	Runtime settings for a model that is deployed with an inference component
update_inference_experiment	Updates an inference experiment that you created
update_model_card	Update an Amazon SageMaker Model Card
update_model_package	Updates a versioned model
update_monitoring_alert	Update the parameters of a model monitor alert
update_monitoring_schedule	Updates a previously created schedule

update_notebook_instance	Updates a notebook instance
update_notebook_instance_lifecycle_config	Updates a notebook instance lifecycle configuration created with the CreateNotebookInstanceLifecycleConfig operation.
update_pipeline	Updates a pipeline
update_pipeline_execution	Updates a pipeline execution
update_project	Updates a machine learning (ML) project that is created from a template.
update_space	Updates the settings of a space
update_training_job	Update a model training job to request a new Debugger profiling configuration.
update_trial	Updates the display name of a trial
update_trial_component	Updates one or more properties of a trial component
update_user_profile	Updates a user profile
update_workforce	Use this operation to update your workforce
update_workteam	Updates an existing work team with new member definitions or descriptions.

Examples

```
## Not run:
svc <- sagemaker()
svc$add_association(
  Foo = 123
)

## End(Not run)
```

sagemakeredgemanager *Amazon Sagemaker Edge Manager*

Description

SageMaker Edge Manager dataplane service for communicating with active agents.

Usage

```
sagemakeredgemanager(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

- | | |
|--------|--|
| config | Optional configuration of credentials, endpoint, and/or region. |
| | <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: |

	<ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token
	<ul style="list-style-type: none"> - profile: The name of a profile to use. If not given, then the default profile is used. <ul style="list-style-type: none"> - anonymous: Set anonymous credentials.
	<ul style="list-style-type: none"> • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoints.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> - access_key_id: AWS access key ID - secret_access_key: AWS secret access key - session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- sagemakeredgemanager(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    )
  )
)
```

```

),
endpoint = "string",
region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
stsRegionalEndpoint = "string"
),
credentials = list(
creds = list(
accessKeyId = "string",
secretAccessKey = "string",
sessionToken = "string"
),
profile = "string",
anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

<code>get_deployments</code>	Use to get the active deployments from a device
<code>get_device_registration</code>	Use to check if a device is registered with SageMaker Edge Manager
<code>send_heartbeat</code>	Use to get the current status of devices registered on SageMaker Edge Manager

Examples

```

## Not run:
svc <- sagemakeredgemanager()
svc$get_deployments(
  Foo = 123
)

## End(Not run)

```

Description

Contains all data plane API operations and data types for the Amazon SageMaker Feature Store. Use this API to put, delete, and retrieve (get) features from a feature store.

Use the following operations to configure your OnlineStore and OfflineStore features, and to create and manage feature groups:

- [CreateFeatureGroup](#)
- [DeleteFeatureGroup](#)
- [DescribeFeatureGroup](#)
- [ListFeatureGroups](#)

Usage

```
sagemakerfeaturestoreruntime(  
    config = list(),  
    credentials = list(),  
    endpoint = NULL,  
    region = NULL  
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none">• credentials:<ul style="list-style-type: none">– creds:<ul style="list-style-type: none">* access_key_id: AWS access key ID* secret_access_key: AWS secret access key* session_token: AWS temporary session token– profile: The name of a profile to use. If not given, then the default profile is used.– anonymous: Set anonymous credentials.• endpoint: The complete URL to use for the constructed client.• region: The AWS Region used in instantiating the client.• close_connection: Immediately close all HTTP connections.• timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.• s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>.• stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none">• creds:<ul style="list-style-type: none">– access_key_id: AWS access key ID

- **secret_access_key**: AWS secret access key
 - **session_token**: AWS temporary session token
 - **profile**: The name of a profile to use. If not given, then the default profile is used.
 - **anonymous**: Set anonymous credentials.
- endpoint** Optional shorthand for complete URL to use for the constructed client.
- region** Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- sagemakerfeaturestoreruntime(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

<code>batch_get_record</code>	Retrieves a batch of Records from a FeatureGroup
<code>delete_record</code>	Deletes a Record from a FeatureGroup in the OnlineStore
<code>get_record</code>	Use for OnlineStore serving from a FeatureStore
<code>put_record</code>	The PutRecord API is used to ingest a list of Records into your feature group

Examples

```
## Not run:
svc <- sagemakerfeaturestoreruntime()
svc$batch_get_record(
  Foo = 123
)
## End(Not run)
```

sagemakergeospatialcapabilities
Amazon SageMaker geospatial capabilities

Description

Provides APIs for creating and managing SageMaker geospatial resources.

Usage

```
sagemakergeospatialcapabilities(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

<code>config</code>	Optional configuration of credentials, endpoint, and/or region.
	<ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials.

	<ul style="list-style-type: none"> • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. http://s3.amazonaws.com/BUCKET/KEY. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoints.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- sagemakergeospatialcapabilities(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
```

```

),
credentials = list(
  creds = list(
    access_key_id = "string",
    secret_access_key = "string",
    session_token = "string"
  ),
  profile = "string",
  anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

<code>delete_earth_observation_job</code>	Use this operation to delete an Earth Observation job
<code>delete_vector_enrichment_job</code>	Use this operation to delete a Vector Enrichment job
<code>export_earth_observation_job</code>	Use this operation to export results of an Earth Observation job and optionally source images
<code>export_vector_enrichment_job</code>	Use this operation to copy results of a Vector Enrichment job to an Amazon S3 location
<code>get_earth_observation_job</code>	Get the details for a previously initiated Earth Observation job
<code>get_raster_data_collection</code>	Use this operation to get details of a specific raster data collection
<code>get_tile</code>	Gets a web mercator tile for the given Earth Observation job
<code>get_vector_enrichment_job</code>	Retrieves details of a Vector Enrichment Job for a given job Amazon Resource Name (ARN)
<code>list_earth_observation_jobs</code>	Use this operation to get a list of the Earth Observation jobs associated with the calling Ama
<code>list_raster_data_collections</code>	Use this operation to get raster data collections
<code>list_tags_for_resource</code>	Lists the tags attached to the resource
<code>list_vector_enrichment_jobs</code>	Retrieves a list of vector enrichment jobs
<code>search_raster_data_collection</code>	Allows you run image query on a specific raster data collection to get a list of the satellite im
<code>start_earth_observation_job</code>	Use this operation to create an Earth observation job
<code>start_vector_enrichment_job</code>	Creates a Vector Enrichment job for the supplied job type
<code>stop_earth_observation_job</code>	Use this operation to stop an existing earth observation job
<code>stop_vector_enrichment_job</code>	Stops the Vector Enrichment job for a given job ARN
<code>tag_resource</code>	The resource you want to tag
<code>untag_resource</code>	The resource you want to untag

Examples

```

## Not run:
svc <- sagemakergeospatialcapabilities()
svc$delete_earth_observation_job(
  Foo = 123
)

## End(Not run)

```

sagemakermetrics	<i>Amazon SageMaker Metrics Service</i>
------------------	---

Description

Contains all data plane API operations and data types for Amazon SageMaker Metrics. Use these APIs to put and retrieve (get) features related to your training run.

- [batch_put_metrics](#)

Usage

```
sagemakermetrics(  
    config = list(),  
    credentials = list(),  
    endpoint = NULL,  
    region = NULL  
)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none">• credentials:<ul style="list-style-type: none">– creds:<ul style="list-style-type: none">* access_key_id: AWS access key ID* secret_access_key: AWS secret access key* session_token: AWS temporary session token– profile: The name of a profile to use. If not given, then the default profile is used.– anonymous: Set anonymous credentials.• endpoint: The complete URL to use for the constructed client.• region: The AWS Region used in instantiating the client.• close_connection: Immediately close all HTTP connections.• timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.• s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>.• stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none">• creds:<ul style="list-style-type: none">– access_key_id: AWS access key ID– secret_access_key: AWS secret access key

- **session_token**: AWS temporary session token
 - **profile**: The name of a profile to use. If not given, then the default profile is used.
 - **anonymous**: Set anonymous credentials.
- endpoint** Optional shorthand for complete URL to use for the constructed client.
- region** Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- sagemakermetrics(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

`batch_put_metrics` Used to ingest training metrics into SageMaker

Examples

```
## Not run:  
svc <- sagemakermetrics()  
svc$batch_put_metrics(  
  Foo = 123  
)  
  
## End(Not run)
```

sagemakerruntime *Amazon SageMaker Runtime*

Description

The Amazon SageMaker runtime API.

Usage

```
sagemakerruntime(  
  config = list(),  
  credentials = list(),  
  endpoint = NULL,  
  region = NULL  
)
```

Arguments

- | | |
|---------------------|---|
| <code>config</code> | Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none">• credentials:<ul style="list-style-type: none">– creds:<ul style="list-style-type: none">* access_key_id: AWS access key ID* secret_access_key: AWS secret access key* session_token: AWS temporary session token– profile: The name of a profile to use. If not given, then the default profile is used.<ul style="list-style-type: none">– anonymous: Set anonymous credentials.• endpoint: The complete URL to use for the constructed client.• region: The AWS Region used in instantiating the client.• close_connection: Immediately close all HTTP connections. |
|---------------------|---|

- **timeout**: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds.
- **s3_force_path_style**: Set this to true to force the request to use path-style addressing, i.e. `http://s3.amazonaws.com/BUCKET/KEY`.
- **stsRegionalEndpoint**: Set sts regional endpoint resolver to regional or legacy <https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoints.html>

credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- sagemakerruntime(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    )
  )
)
```

```
    secret_access_key = "string",
    session_token = "string"
),
profile = "string",
anonymous = "logical"
),
endpoint = "string",
region = "string"
)
```

Operations

invoke_endpoint	After you deploy a model into production using Amazon SageMaker hosting service.
invoke_endpoint_async	After you deploy a model into production using Amazon SageMaker hosting service.
invoke_endpoint_with_response_stream	Invokes a model at the specified endpoint to return the inference response as a stream.

Examples

```
## Not run:
svc <- sagemakerruntime()
svc$invoke_endpoint(
  Foo = 123
)

## End(Not run)
```

textract

Amazon Textract

Description

Amazon Textract detects and analyzes text in documents and converts it into machine-readable text. This is the API reference documentation for Amazon Textract.

Usage

```
textract(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

- | | |
|--------|---|
| config | Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none">• credentials:<ul style="list-style-type: none">– creds:<ul style="list-style-type: none">* access_key_id: AWS access key ID |
|--------|---|

	<ul style="list-style-type: none"> * secret_access_key: AWS secret access key * session_token: AWS temporary session token - profile: The name of a profile to use. If not given, then the default profile is used. - anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> - access_key_id: AWS access key ID - secret_access_key: AWS secret access key - session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- textract(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
  )
)
```

```

        region = "string",
        close_connection = "logical",
        timeout = "numeric",
        s3_force_path_style = "logical",
        stsRegionalEndpoint = "string"
    ),
    credentials = list(
        creds = list(
            accessKeyId = "string",
            secretAccessKey = "string",
            sessionToken = "string"
        ),
        profile = "string",
        anonymous = "logical"
    ),
    endpoint = "string",
    region = "string"
)

```

Operations

analyze_document	Analyzes an input document for relationships between detected items
analyze_expense	AnalyzeExpense synchronously analyzes an input document for financially related relations
analyze_id	Analyzes identity documents for relevant information
create_adapter	Creates an adapter, which can be fine-tuned for enhanced performance on user provided documents
create_adapter_version	Creates a new version of an adapter
delete_adapter	Deletes an Amazon Textract adapter
delete_adapter_version	Deletes an Amazon Textract adapter version
detect_document_text	Detects text in the input document
get_adapter	Gets configuration information for an adapter specified by an AdapterId, returning information about its current state
get_adapter_version	Gets configuration information for the specified adapter version, including: AdapterId, AdapterName, and State
get_document_analysis	Gets the results for an Amazon Textract asynchronous operation that analyzes text in a document
get_document_text_detection	Gets the results for an Amazon Textract asynchronous operation that detects text in a document
get_expense_analysis	Gets the results for an Amazon Textract asynchronous operation that analyzes invoices and receipts
get_lending_analysis	Gets the results for an Amazon Textract asynchronous operation that analyzes text in a lending document
get_lending_analysis_summary	Gets summarized results for the StartLendingAnalysis operation, which analyzes text in a lending document
list_adapters	Lists all adapters that match the specified filtration criteria
list_adapter_versions	List all versions of an adapter that meet the specified filtration criteria
list_tags_for_resource	Lists all tags for an Amazon Textract resource
start_document_analysis	Starts the asynchronous analysis of an input document for relationships between detected items
start_document_text_detection	Starts the asynchronous detection of text in a document
start_expense_analysis	Starts the asynchronous analysis of invoices or receipts for data like contact information, item descriptions, and more
start_lending_analysis	Starts the classification and analysis of an input document
tag_resource	Adds one or more tags to the specified resource
untag_resource	Removes any tags with the specified keys from the specified resource
update_adapter	Update the configuration for an adapter

Examples

```
## Not run:
svc <- textract()
svc$analyze_document(
  Foo = 123
)
## End(Not run)
```

transcribeservice *Amazon Transcribe Service*

Description

Amazon Transcribe offers three main types of batch transcription: **Standard**, **Medical**, and **Call Analytics**.

- **Standard transcriptions** are the most common option. Refer to for details.
- **Medical transcriptions** are tailored to medical professionals and incorporate medical terms. A common use case for this service is transcribing doctor-patient dialogue into after-visit notes. Refer to for details.
- **Call Analytics transcriptions** are designed for use with call center audio on two different channels; if you’re looking for insight into customer service calls, use this option. Refer to for details.

Usage

```
transcribeservice(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

- | | |
|--------|---|
| config | Optional configuration of credentials, endpoint, and/or region. |
|--------|---|
- **credentials:**
 - **creds:**
 - * **access_key_id:** AWS access key ID
 - * **secret_access_key:** AWS secret access key
 - * **session_token:** AWS temporary session token
 - **profile:** The name of a profile to use. If not given, then the default profile is used.
 - **anonymous:** Set anonymous credentials.

	<ul style="list-style-type: none"> • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. http://s3.amazonaws.com/BUCKET/KEY. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoints.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- transcribeservice(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
```

```

),
credentials = list(
creds = list(
    access_key_id = "string",
    secret_access_key = "string",
    session_token = "string"
),
profile = "string",
anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

create_call_analytics_category	Creates a new Call Analytics category
create_language_model	Creates a new custom language model
create_medical_vocabulary	Creates a new custom medical vocabulary
create_vocabulary	Creates a new custom vocabulary
create_vocabulary_filter	Creates a new custom vocabulary filter
delete_call_analytics_category	Deletes a Call Analytics category
delete_call_analytics_job	Deletes a Call Analytics job
delete_language_model	Deletes a custom language model
delete_medical_scribe_job	Deletes a Medical Scribe job
delete_medical_transcription_job	Deletes a medical transcription job
delete_medical_vocabulary	Deletes a custom medical vocabulary
delete_transcription_job	Deletes a transcription job
delete_vocabulary	Deletes a custom vocabulary
delete_vocabulary_filter	Deletes a custom vocabulary filter
describe_language_model	Provides information about the specified custom language model
get_call_analytics_category	Provides information about the specified Call Analytics category
get_call_analytics_job	Provides information about the specified Call Analytics job
get_medical_scribe_job	Provides information about the specified Medical Scribe job
get_medical_transcription_job	Provides information about the specified medical transcription job
get_medical_vocabulary	Provides information about the specified custom medical vocabulary
get_transcription_job	Provides information about the specified transcription job
get_vocabulary	Provides information about the specified custom vocabulary
get_vocabulary_filter	Provides information about the specified custom vocabulary filter
list_call_analytics_categories	Provides a list of Call Analytics categories, including all rules that make up each category
list_call_analytics_jobs	Provides a list of Call Analytics jobs that match the specified criteria
list_language_models	Provides a list of custom language models that match the specified criteria
list_medical_scribe_jobs	Provides a list of Medical Scribe jobs that match the specified criteria
list_medical_transcription_jobs	Provides a list of medical transcription jobs that match the specified criteria
list_medical_vocabularies	Provides a list of custom medical vocabularies that match the specified criteria
list_tags_for_resource	Lists all tags associated with the specified transcription job, vocabulary, model, or resource
list_transcription_jobs	Provides a list of transcription jobs that match the specified criteria
list_vocabularies	Provides a list of custom vocabularies that match the specified criteria

list_vocabulary_filters	Provides a list of custom vocabulary filters that match the specified criteria
start_call_analytics_job	Transcribes the audio from a customer service call and applies any additional Request Parameters you specify
start_medical_scribe_job	Transcribes patient-clinician conversations and generates clinical notes
start_medical_transcription_job	Transcribes the audio from a medical dictation or conversation and applies any additional Request Parameters you specify
start_transcription_job	Transcribes the audio from a media file and applies any additional Request Parameters you specify
tag_resource	Adds one or more custom tags, each in the form of a key:value pair, to the specified resource
untag_resource	Removes the specified tags from the specified Amazon Transcribe resource
update_call_analytics_category	Updates the specified Call Analytics category with new rules
update_medical_vocabulary	Updates an existing custom medical vocabulary with new values
update_vocabulary	Updates an existing custom vocabulary with new values
update_vocabulary_filter	Updates an existing custom vocabulary filter with a new list of words

Examples

```
## Not run:
svc <- transcribeservice()
svc$create_call_analytics_category(
  Foo = 123
)
## End(Not run)
```

translate

Amazon Translate

Description

Provides translation of the input content from the source language to the target language.

Usage

```
translate(
  config = list(),
  credentials = list(),
  endpoint = NULL,
  region = NULL
)
```

Arguments

- | | |
|--------|---|
| config | Optional configuration of credentials, endpoint, and/or region. |
| | <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID |

	<ul style="list-style-type: none"> * secret_access_key: AWS secret access key * session_token: AWS temporary session token - profile: The name of a profile to use. If not given, then the default profile is used. - anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. <code>http://s3.amazonaws.com/BUCKET/KEY</code>. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized-endpoint.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> - access_key_id: AWS access key ID - secret_access_key: AWS secret access key - session_token: AWS temporary session token • profile: The name of a profile to use. If not given, then the default profile is used. • anonymous: Set anonymous credentials.
endpoint	Optional shorthand for complete URL to use for the constructed client.
region	Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- translate(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
  )
)
```

```

region = "string",
close_connection = "logical",
timeout = "numeric",
s3_force_path_style = "logical",
stsRegionalEndpoint = "string"
),
credentials = list(
  creds = list(
    accessKeyId = "string",
    secretAccessKey = "string",
    sessionToken = "string"
  ),
  profile = "string",
  anonymous = "logical"
),
endpoint = "string",
region = "string"
)

```

Operations

create_parallel_data	Creates a parallel data resource in Amazon Translate by importing an input file from Amazon S3.
delete_parallel_data	Deletes a parallel data resource in Amazon Translate.
delete_terminology	A synchronous action that deletes a custom terminology.
describe_text_translation_job	Gets the properties associated with an asynchronous batch translation job including name, ID, and status.
get_parallel_data	Provides information about a parallel data resource.
get_terminology	Retrieves a custom terminology.
import_terminology	Creates or updates a custom terminology, depending on whether one already exists for the given language pair.
list_languages	Provides a list of languages (RFC-5646 codes and names) that Amazon Translate supports.
list_parallel_data	Provides a list of your parallel data resources in Amazon Translate.
list_tags_for_resource	Lists all tags associated with a given Amazon Translate resource.
list_terminologies	Provides a list of custom terminologies associated with your account.
list_text_translation_jobs	Gets a list of the batch translation jobs that you have submitted.
start_text_translation_job	Starts an asynchronous batch translation job.
stop_text_translation_job	Stops an asynchronous batch translation job that is in progress.
tag_resource	Associates a specific tag with a resource.
translate_document	Translates the input document from the source language to the target language.
translate_text	Translates input text from the source language to the target language.
untag_resource	Removes a specific tag associated with an Amazon Translate resource.
update_parallel_data	Updates a previously created parallel data resource by importing a new input file from Amazon S3.

Examples

```

## Not run:
svc <- translate()
svc$create_parallel_data(

```

```

Foo = 123
)

## End(Not run)

```

voiceid

Amazon Voice ID

Description

Amazon Connect Voice ID provides real-time caller authentication and fraud risk detection, which make voice interactions in contact centers more secure and efficient.

Usage

```
voiceid(config = list(), credentials = list(), endpoint = NULL, region = NULL)
```

Arguments

config	Optional configuration of credentials, endpoint, and/or region. <ul style="list-style-type: none"> • credentials: <ul style="list-style-type: none"> – creds: <ul style="list-style-type: none"> * access_key_id: AWS access key ID * secret_access_key: AWS secret access key * session_token: AWS temporary session token – profile: The name of a profile to use. If not given, then the default profile is used. – anonymous: Set anonymous credentials. • endpoint: The complete URL to use for the constructed client. • region: The AWS Region used in instantiating the client. • close_connection: Immediately close all HTTP connections. • timeout: The time in seconds till a timeout exception is thrown when attempting to make a connection. The default is 60 seconds. • s3_force_path_style: Set this to true to force the request to use path-style addressing, i.e. http://s3.amazonaws.com/BUCKET/KEY. • stsRegionalEndpoint: Set sts regional endpoint resolver to regional or legacy https://docs.aws.amazon.com/sdkref/latest/guide/feature-sts-regionalized.html
credentials	Optional credentials shorthand for the config parameter <ul style="list-style-type: none"> • creds: <ul style="list-style-type: none"> – access_key_id: AWS access key ID – secret_access_key: AWS secret access key – session_token: AWS temporary session token

- **profile:** The name of a profile to use. If not given, then the default profile is used.
 - **anonymous:** Set anonymous credentials.
- endpoint** Optional shorthand for complete URL to use for the constructed client.
- region** Optional shorthand for AWS Region used in instantiating the client.

Value

A client for the service. You can call the service's operations using syntax like `svc$operation(...)`, where `svc` is the name you've assigned to the client. The available operations are listed in the Operations section.

Service syntax

```
svc <- voiceid(
  config = list(
    credentials = list(
      creds = list(
        access_key_id = "string",
        secret_access_key = "string",
        session_token = "string"
      ),
      profile = "string",
      anonymous = "logical"
    ),
    endpoint = "string",
    region = "string",
    close_connection = "logical",
    timeout = "numeric",
    s3_force_path_style = "logical",
    stsRegionalEndpoint = "string"
  ),
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string",
    anonymous = "logical"
  ),
  endpoint = "string",
  region = "string"
)
```

Operations

associate_fraudster	Associates the fraudsters with the watchlist specified in the same domain
-------------------------------------	---

<code>create_domain</code>	Creates a domain that contains all Amazon Connect Voice ID data, such as speakers, fra
<code>create_watchlist</code>	Creates a watchlist that fraudsters can be a part of
<code>delete_domain</code>	Deletes the specified domain from Voice ID
<code>delete_fraudster</code>	Deletes the specified fraudster from Voice ID
<code>delete_speaker</code>	Deletes the specified speaker from Voice ID
<code>delete_watchlist</code>	Deletes the specified watchlist from Voice ID
<code>describe_domain</code>	Describes the specified domain
<code>describe_fraudster</code>	Describes the specified fraudster
<code>describe_fraudster_registration_job</code>	Describes the specified fraudster registration job
<code>describe_speaker</code>	Describes the specified speaker
<code>describe_speaker_enrollment_job</code>	Describes the specified speaker enrollment job
<code>describe_watchlist</code>	Describes the specified watchlist
<code>disassociate_fraudster</code>	Disassociates the fraudsters from the watchlist specified
<code>evaluate_session</code>	Evaluates a specified session based on audio data accumulated during a streaming Amaz
<code>list_domains</code>	Lists all the domains in the Amazon Web Services account
<code>list_fraudster_registration_jobs</code>	Lists all the fraudster registration jobs in the domain with the given JobStatus
<code>list_fraudsters</code>	Lists all fraudsters in a specified watchlist or domain
<code>list_speaker_enrollment_jobs</code>	Lists all the speaker enrollment jobs in the domain with the specified JobStatus
<code>list_speakers</code>	Lists all speakers in a specified domain
<code>list_tags_for_resource</code>	Lists all tags associated with a specified Voice ID resource
<code>list_watchlists</code>	Lists all watchlists in a specified domain
<code>opt_out_speaker</code>	Opts out a speaker from Voice ID
<code>start_fraudster_registration_job</code>	Starts a new batch fraudster registration job using provided details
<code>start_speaker_enrollment_job</code>	Starts a new batch speaker enrollment job using specified details
<code>tag_resource</code>	Tags a Voice ID resource with the provided list of tags
<code>untag_resource</code>	Removes specified tags from a specified Amazon Connect Voice ID resource
<code>update_domain</code>	Updates the specified domain
<code>update_watchlist</code>	Updates the specified watchlist

Examples

```
## Not run:
svc <- voiceid()
svc$associate_fraudster(
  Foo = 123
)
## End(Not run)
```

Index

activate_anomaly_detector, 48
add_association, 73
add_tags, 51, 73
analyze_document, 95
analyze_expense, 95
analyze_id, 95
associate_faces, 65, 69
associate_fraudster, 103
associate_trial_component, 73
augmentedairuntime, 3

back_test_anomaly_detector, 48
batch_create_custom_vocabulary_item,
 35
batch_create_variable, 29
batch_delete_custom_vocabulary_item,
 35
batch_describe_model_package, 73
batch_detect_dominant_language, 13
batch_detect_entities, 13
batch_detect_key_phrases, 13
batch_detect_sentiment, 13
batch_detect_syntax, 13
batch_detect_targeted_sentiment, 13
batch_get_record, 86
batch_get_variable, 29
batch_put_metrics, 89, 91
batch_update_custom_vocabulary_item,
 35
bedrock, 6
bedrockruntime, 9
build_bot_locale, 35

cancel_batch_import_job, 29
cancel_batch_prediction_job, 29
classify_document, 13
compare_faces, 65, 69
comprehend, 11
comprehendmedical, 15
contains_pii_entities, 13

copy_project_version, 66, 69
create_action, 73
create_adapter, 95
create_adapter_version, 95
create_alert, 48
create_algorithm, 73
create_anomaly_detector, 48
create_app, 73
create_app_image_config, 73
create_application_instance, 53
create_artifact, 73
create_auto_ml_job, 73
create_auto_ml_job_v2, 73
create_auto_predictor, 25
create_batch_import_job, 29
create_batch_inference_job, 56
create_batch_prediction, 51
create_batch_prediction_job, 29
create_batch_segment_job, 56
create_bot, 35
create_bot_alias, 35
create_bot_locale, 35
create_bot_replica, 35
create_bot_version, 32, 36
create_call_analytics_category, 98
create_campaign, 56
create_cluster, 73
create_code_repository, 73
create_collection, 65, 69
create_compilation_job, 73
create_context, 73
create_data_quality_job_definition, 73
create_data_source_from_rds, 51
create_data_source_from_redshift, 51
create_data_source_from_s3, 51
create_dataset, 13, 25, 44, 56, 66, 69
create_dataset_export_job, 56
create_dataset_group, 25, 56
create_dataset_import_job, 25, 56

create_detector_version, 29
 create_device_fleet, 73
 create_document_classifier, 13
 create_domain, 73, 104
 create_edge_deployment_plan, 73
 create_edge_deployment_stage, 73
 create_edge_packaging_job, 74
 create_endpoint, 13, 74
 create_endpoint_config, 74
 create_entity_recognizer, 13
 create_evaluation, 51
 create_evaluation_job, 8
 create_event_tracker, 56
 create_experiment, 74
 create_explainability, 25
 create_explainability_export, 25
 create_export, 36
 create_face_liveness_session, 69
 create_feature_group, 74
 create_filter, 56
 create_flow_definition, 74
 create_flywheel, 13
 create_forecast, 25
 create_forecast_export_job, 25
 create_guardrail, 8
 create_guardrail_version, 8
 create_hub, 74
 create_human_task_ui, 74
 create_hyper_parameter_tuning_job, 74
 create_image, 74
 create_image_version, 74
 create_inference_component, 74
 create_inference_experiment, 74
 create_inference_recommendations_job,
 74
 create_inference_scheduler, 45
 create_intent, 36
 create_intent_version, 32
 create_job_for_devices, 53
 create_label, 45
 create_label_group, 45
 create_labeling_job, 74
 create_language_model, 98
 create_list, 29
 create_medical_vocabulary, 98
 create_metric_attribution, 56
 create_metric_set, 48
 create_ml_model, 51
 create_model, 29, 45, 74
 create_model_bias_job_definition, 74
 create_model_card, 74
 create_model_card_export_job, 74
 create_model_customization_job, 8
 create_model_explainability_job_definition,
 74
 create_model_package, 74
 create_model_package_group, 74
 create_model_quality_job_definition,
 74
 create_model_version, 29
 create_monitor, 25
 create_monitoring_schedule, 74
 create_node_from_template_job, 53
 create_notebook_instance, 74
 create_notebook_instance.lifecycle_config,
 74
 create_package, 53
 create_package_import_job, 53
 create_parallel_data, 101
 create_pipeline, 74
 create_predictor, 25
 create_predictor_backtest_export_job,
 25
 create_presigned_domain_url, 74
 create_presigned_notebook_instance_url,
 74
 create_processing_job, 74
 create_project, 66, 69, 74
 create_project_version, 66, 69
 create_provisioned_model_throughput, 8
 create_realtime_endpoint, 51
 create_recommender, 56
 create_resource_policy, 36
 create_resource_policy_statement, 36
 create_retraining_scheduler, 45
 create_rule, 29
 create_schema, 56
 create_slot, 36
 create_slot_type, 36
 create_slot_type_version, 32
 create_solution, 56
 create_solution_version, 56
 create_space, 74
 create_stream_processor, 67, 69
 create_studio.lifecycle_config, 74
 create_test_set_discrepancy_report, 36

create_training_job, 74
create_transform_job, 74
create_trial, 74
create_trial_component, 74
create_upload_url, 36
create_user, 65, 69
create_user_profile, 74
create_variable, 29
create_vocabulary, 98
create_vocabulary_filter, 98
create_watchlist, 104
create_what_if_analysis, 25
create_what_if_forecast, 25
create_what_if_forecast_export, 25
create_workforce, 74
create_workteam, 74

deactivate_anomaly_detector, 48
delete_action, 74
delete_adapter, 95
delete_adapter_version, 95
delete_alert, 48
delete_algorithm, 74
delete_anomaly_detector, 48
delete_app, 74
delete_app_image_config, 74
delete_artifact, 74
delete_association, 74
delete_batch_import_job, 29
delete_batch_prediction, 51
delete_batch_prediction_job, 29
delete_bot, 32, 36
delete_bot_alias, 32, 36
delete_bot_channel_association, 32
delete_bot_locale, 36
delete_bot_replica, 36
delete_bot_version, 32, 36
delete_call_analytics_category, 98
delete_call_analytics_job, 98
delete_campaign, 57
delete_cluster, 74
delete_code_repository, 74
delete_collection, 65, 69
delete_compilation_job, 75
delete_context, 75
delete_custom_model, 8
delete_custom_vocabulary, 36
delete_data_quality_job_definition, 75
delete_data_source, 51

delete_dataset, 25, 45, 57, 66, 69
delete_dataset_group, 25, 57
delete_dataset_import_job, 25
delete_detector, 29
delete_detector_version, 29
delete_device, 53
delete_device_fleet, 75
delete_document_classifier, 13
delete_domain, 75, 104
delete_earth_observation_job, 88
delete_edge_deployment_plan, 75
delete_edge_deployment_stage, 75
delete_endpoint, 13, 75
delete_endpoint_config, 75
delete_entity_recognizer, 13
delete_entity_type, 29
delete_evaluation, 51
delete_event, 29
delete_event_tracker, 57
delete_event_type, 29
delete_events_by_event_type, 29
delete_experiment, 75
delete_explainability, 25
delete_explainability_export, 25
delete_export, 36
delete_external_model, 29
delete_faces, 65, 69
delete_feature_group, 75
delete_filter, 57
delete_flow_definition, 75
delete_flywheel, 13
delete_forecast, 25
delete_forecast_export_job, 25
delete_fraudster, 104
delete_guardrail, 8
delete_hub, 75
delete_hub_content, 75
delete_human_loop, 6
delete_human_task_ui, 75
delete_hyper_parameter_tuning_job, 75
delete_image, 75
delete_image_version, 75
delete_import, 36
delete_inference_component, 75
delete_inference_experiment, 75
delete_inference_scheduler, 45
delete_intent, 32, 36
delete_intent_version, 32

delete_label, 29, 45
 delete_label_group, 45
 delete_language_model, 98
 delete_lexicon, 64
 delete_list, 29
 delete_medical_scribe_job, 98
 delete_medical_transcription_job, 98
 delete_medical_vocabulary, 98
 delete_metric_attribution, 57
 delete_ml_model, 51
 delete_model, 29, 45, 75
 delete_model_bias_job_definition, 75
 delete_model_card, 75
 delete_model_explainability_job_definition, 75
 delete_model_invocation_logging_configuration, 8
 delete_model_package, 75
 delete_model_package_group, 75
 delete_model_package_group_policy, 75
 delete_model_quality_job_definition, 75
 delete_model_version, 29
 delete_monitor, 25
 delete_monitoring_schedule, 75
 delete_notebook_instance, 75
 delete_notebook_instance_lifecycle_config, 75
 delete_outcome, 29
 delete_package, 53
 delete_parallel_data, 101
 delete_pipeline, 75
 delete_predictor, 25
 delete_predictor_backtest_export_job, 25
 delete_project, 66, 69, 75
 delete_project_policy, 66, 69
 delete_project_version, 66, 69
 delete_provisioned_model_throughput, 8
 delete_realtime_endpoint, 51
 delete_recommender, 57
 delete_record, 86
 delete_resource_policy, 13, 36, 45
 delete_resource_policy_statement, 36
 delete_resource_tree, 25
 delete_retraining_scheduler, 45
 delete_rule, 29
 delete_schema, 57
 delete_session, 40, 42
 delete_slot, 36
 delete_slot_type, 32, 36
 delete_slot_type_version, 32
 delete_solution, 57
 delete_space, 75
 delete_speaker, 104
 delete_stream_processor, 67, 69
 delete_studio_lifecycle_config, 75
 delete_tags, 51, 75
 delete_terminology, 101
 delete_test_set, 36
 delete_transcription_job, 98
 delete_trial, 75
 delete_trial_component, 75
 delete_user, 65, 69
 delete_user_profile, 75
 delete_utterances, 32, 36
 delete_variable, 29
 delete_vector_enrichment_job, 88
 delete_vocabulary, 98
 delete_vocabulary_filter, 98
 delete_watchlist, 104
 delete_what_if_analysis, 25
 delete_what_if_forecast, 25
 delete_what_if_forecast_export, 25
 delete_workforce, 75
 delete_workteam, 75
 deregister_devices, 75
 deregister_package_version, 53
 describe_accelerator_offerings, 20
 describe_accelerator_types, 20
 describe_accelerators, 20
 describe_action, 75
 describe_alert, 48
 describe_algorithm, 57, 75
 describe_anomaly_detection_executions, 48
 describe_anomaly_detector, 48
 describe_app, 75
 describe_app_image_config, 75
 describe_application_instance, 54
 describe_application_instance_details, 54
 describe_artifact, 75
 describe_auto_ml_job, 75
 describe_auto_ml_job_v2, 76
 describe_auto_predictor, 25

describe_batch_inference_job, 57
describe_batch_predictions, 51
describe_batch_segment_job, 57
describe_bot, 36
describe_bot_alias, 36
describe_bot_locale, 36
describe_bot_recommendation, 36
describe_bot_replica, 36
describe_bot_resource_generation, 36
describe_bot_version, 36
describe_campaign, 57
describe_cluster, 76
describe_cluster_node, 76
describe_code_repository, 76
describe_collection, 65, 69
describe_compilation_job, 76
describe_context, 76
describe_custom_vocabulary_metadata, 36
describe_data_ingestion_job, 45
describe_data_quality_job_definition, 76
describe_data_sources, 51
describe_dataset, 13, 25, 45, 57, 66, 69
describe_dataset_export_job, 57
describe_dataset_group, 25, 57
describe_dataset_import_job, 25, 57
describe_detector, 29
describe_device, 54, 76
describe_device_fleet, 76
describe_device_job, 54
describe_document_classification_job, 13
describe_document_classifier, 14
describe_domain, 76, 104
describe_dominant_language_detection_job, 14
describe_edge_deployment_plan, 76
describe_edge_packaging_job, 76
describe_endpoint, 14, 76
describe_endpoint_config, 76
describe_entities_detection_job, 14
describe_entities_detection_v2_job, 17
describe_entity_recognizer, 14
describe_evaluations, 51
describe_event_tracker, 57
describe_events_detection_job, 14
describe_experiment, 76
describe_explainability, 25
describe_explainability_export, 25
describe_export, 36
describe_feature_group, 76
describe_feature_metadata, 76
describe_feature_transformation, 57
describe_filter, 57
describe_flow_definition, 76
describe_flywheel, 14
describe_flywheel_iteration, 14
describe_forecast, 25
describe_forecast_export_job, 25
describe_fraudster, 104
describe_fraudster_registration_job, 104
describe_hub, 76
describe_hub_content, 76
describe_human_loop, 6
describe_human_task_ui, 76
describe_hyper_parameter_tuning_job, 76
describe_icd10cm_inference_job, 17
describe_image, 76
describe_image_version, 76
describe_import, 36
describe_inference_component, 76
describe_inference_experiment, 76
describe_inference_recommendations_job, 76
describe_inference_scheduler, 45
describe_intent, 36
describe_key_phrases_detection_job, 14
describe_label, 45
describe_label_group, 45
describe_labeling_job, 76
describe_language_model, 98
describe_lineage_group, 76
describe_metric_attribution, 57
describe_metric_set, 48
describe_ml_models, 51
describe_model, 45, 76
describe_model_bias_job_definition, 76
describe_model_card, 76
describe_model_card_export_job, 76
describe_model_explainability_job_definition, 76
describe_model_package, 76
describe_model_package_group, 76

describe_model_quality_job_definition, **14**
 describe_model_version, **45**
 describe_model_versions, **29**
 describe_monitor, **25**
 describe_monitoring_schedule, **76**
 describe_node, **54**
 describe_node_from_template_job, **54**
 describe_notebook_instance, **76**
 describe_notebook_instance_lifecycle_config, **76**
 describe_package, **54**
 describe_package_import_job, **54**
 describe_package_version, **54**
 describe_phi_detection_job, **17**
 describe_pii_entities_detection_job, **14**
 describe_pipeline, **76**
 describe_pipeline_definition_for_execution, **76**
 describe_pipeline_execution, **76**
 describe_predictor, **25**
 describe_predictor_backtest_export_job, **26**
 describe_processing_job, **76**
 describe_project, **76**
 describe_project_versions, **66, 70**
 describe_projects, **66, 70**
 describe_recipe, **57**
 describe_recommender, **57**
 describe_resource_policy, **14, 36, 45**
 describe_retraining_scheduler, **45**
 describe_rx_norm_inference_job, **17**
 describe_schema, **57**
 describe_sentiment_detection_job, **14**
 describe_slot, **36**
 describe_slot_type, **36**
 describe_snomedct_inference_job, **17**
 describe_solution, **57**
 describe_solution_version, **57**
 describe_space, **76**
 describe_speaker, **104**
 describe_speaker_enrollment_job, **104**
 describe_stream_processor, **67, 70**
 describe_studio_lifecycle_config, **76**
 describe_subscribed_workteam, **76**
 describe_tags, **51**
 describe_targeted_sentiment_detection_job,

describe_test_execution, **36**
 describe_test_set, **36**
 describe_test_set_discrepancy_report, **36**
 describe_test_set_generation, **36**
 describe_text_translation_job, **101**
 describe_topics_detection_job, **14**
 describe_training_job, **77**
 describe_transform_job, **77**
 describe_trial, **77**
 describe_trial_component, **77**
 describe_user_profile, **77**
 describe_VOICES, **65**
 describe_watchlist, **104**
 describe_what_if_analysis, **26**
 describe_what_if_forecast, **26**
 describe_what_if_forecast_export, **26**
 describe_workforce, **77**
 describe_workteam, **77**
 detect_custom_labels, **66, 70**
 detect_document_text, **95**
 detect_dominant_language, **14**
 detect_entities, **14, 17**
 detect_entities_v2, **17**
 detect_faces, **65, 70**
 detect_key_phrases, **14**
 detect_labels, **65, 70**
 detect_metric_set_config, **48**
 detect_moderation_labels, **65, 70**
 detect_phi, **17**
 detect_pii_entities, **14**
 detect_protective_equipment, **66, 70**
 detect_sentiment, **14**
 detect_syntax, **14**
 detect_targeted_sentiment, **14**
 detect_text, **66, 70**
 detect_toxic_content, **14**
 disable_sagemaker_servicecatalog_portfolio, **77**
 disassociate_faces, **66, 70**
 disassociate_fraudster, **104**
 disassociate_trial_component, **77**
 distribute_dataset_entries, **66, 70**
 elasticinference, **18**
 enable_sagemaker_servicecatalog_portfolio, **77**
 evaluate_session, **104**

export_earth_observation_job, 88
export_vector_enrichment_job, 88

forecastqueryservice, 21
forecastservice, 23
frauddetector, 26

generate_bot_element, 36
get_accuracy_metrics, 26
get_action_recommendations, 62
get_adapter, 95
get_adapter_version, 95
get_anomaly_group, 48
get_batch_import_jobs, 29
get_batch_prediction, 51
get_batch_prediction_jobs, 29
get_bot, 32
get_bot_alias, 32
get_bot_aliases, 33
get_bot_channel_association, 33
get_bot_channel_associations, 33
get_bot_versions, 33
get_bots, 33
get_builtin_intent, 33
get_builtin_intents, 33
get_builtin_slot_types, 33
get_call_analytics_category, 98
get_call_analytics_job, 98
get_celebrity_info, 66, 70
get_celebrity_recognition, 67, 70
get_content_moderation, 67, 70
get_custom_model, 8
get_data_quality_metrics, 48
get_data_source, 51
get_delete_events_by_event_type_status, 29
get_deployments, 82
get_detector_version, 29
get_detectors, 29
get_device_fleet_report, 77
get_device_registration, 82
get_document_analysis, 95
get_document_text_detection, 95
get_earth_observation_job, 88
get_entity_types, 29
get_evaluation, 51
get_evaluation_job, 8
get_event, 29
get_event_prediction, 29

get_event_prediction_metadata, 29
get_event_types, 29
get_expense_analysis, 95
get_export, 33
get_external_models, 29
get_face_detection, 67, 70
get_face_liveness_session_results, 70
get_face_search, 67, 70
get_feedback, 48
get.foundation_model, 8
get.guardrail, 8
get.import, 33
get.intent, 33
get.intent_versions, 33
get.intents, 33
get.kms_encryption_key, 29
get.label_detection, 67, 70
get.labels, 29
get.lending_analysis, 95
get.lending_analysis_summary, 95
get.lexicon, 65
get.lineage_group_policy, 77
get.list_elements, 29
get.lists_metadata, 29
get.media_analysis_job, 66, 70
get.medical_scribe_job, 98
get.medical_transcription_job, 98
get.medical_vocabulary, 98
get.migration, 33
get.migrations, 33
get.ml_model, 51
get.model_customization_job, 8
get.model_invocation_logging_configuration, 8
get.model_package_group_policy, 77
get.model_version, 29
get.models, 29
get.outcomes, 29
get.parallel_data, 101
get.person_tracking, 67, 70
get.personalized_ranking, 62
get.provisioned_model_throughput, 8
get.raster_data_collection, 88
get.recommendations, 62
get.record, 86
get.rules, 30
get.sagemaker_servicecatalog_portfolio_status, 77

get_sample_data, 48
 get_scaling_configuration_recommendation,
 77
 get_searchSuggestions, 77
 get_segment_detection, 67, 70
 get_session, 40, 42
 get_slot_type, 33
 get_slot_type_versions, 33
 get_slot_types, 33
 get_solution_metrics, 57
 get_speech_synthesis_task, 65
 get_terminology, 101
 get_test_execution_artifacts_url, 36
 get_text_detection, 67, 70
 get_tile, 88
 get_transcription_job, 98
 get_utterances_view, 33
 get_variables, 30
 get_vector_enrichment_job, 88
 get_vocabulary, 98
 get_vocabulary_filter, 98

 import_dataset, 45
 import_hub_content, 77
 import_model, 14
 import_model_version, 45
 import_terminology, 101
 index_faces, 66, 70
 infer_icd10cm, 17
 infer_rx_norm, 17
 infer_snomedct, 17
 invoke_endpoint, 93
 invoke_endpoint_async, 93
 invoke_endpoint_with_response_stream,
 93
 invoke_model, 11
 invoke_model_with_response_stream, 11

 lexmodelbuildingservice, 30
 lexmodelsv2, 33
 lexruntimeservice, 38
 lexruntimev2, 40
 list_actions, 77
 list_adapter_versions, 95
 list_adapters, 95
 list_aggregated_utterances, 36
 list_alerts, 48
 list_algorithms, 77
 list_aliases, 77

 list_anomaly_detectors, 48
 list_anomaly_group_related_metrics, 48
 list_anomaly_group_summaries, 48
 list_anomaly_group_time_series, 48
 list_app_image_configs, 77
 list_application_instance_dependencies,
 54
 list_application_instance_node_instances,
 54
 list_application_instances, 54
 list_apps, 77
 list_artifacts, 77
 list_associations, 77
 list_auto_ml_jobs, 77
 list_batch_inference_jobs, 57
 list_batch_segment_jobs, 57
 list_bot_alias_replicas, 36
 list_bot_aliases, 36
 list_bot_locales, 36
 list_bot_recommendations, 37
 list_bot_replicas, 37
 list_bot_resource_generations, 37
 list_bot_version_replicas, 37
 list_bot_versions, 37
 list_bots, 37
 list_builtin_intents, 37
 list_builtin_slot_types, 37
 list_call_analytics_categories, 98
 list_call_analytics_jobs, 98
 list_campaigns, 57
 list_candidates_for_auto_ml_job, 77
 list_cluster_nodes, 77
 list_clusters, 77
 list_code_repositories, 77
 list_collections, 66, 70
 list_compilation_jobs, 77
 list_contexts, 77
 list_custom_models, 8
 list_custom_vocabulary_items, 37
 list_data_ingestion_jobs, 45
 list_data_quality_job_definitions, 77
 list_dataset_entries, 66, 70
 list_dataset_export_jobs, 57
 list_dataset_groups, 26, 57
 list_dataset_import_jobs, 26, 57
 list_dataset_labels, 66, 70
 list_datasets, 14, 26, 45, 57
 list_device_fleets, 77

list_devices, 54, 77
list_devices_jobs, 54
list_document_classification_jobs, 14
list_document_classifier_summaries, 14
list_document_classifiers, 14
list_domains, 77, 104
list_dominant_language_detection_jobs,
 14
list_earth_observation_jobs, 88
list_edge_deployment_plans, 77
list_edge_packaging_jobs, 77
list_endpoint_configs, 77
list_endpoints, 14, 77
list_entities_detection_jobs, 14
list_entities_detection_v2_jobs, 17
list_entity_recognizer_summaries, 14
list_entity_recognizers, 14
list_evaluation_jobs, 8
list_event_predictions, 30
list_event_trackers, 57
list_events_detection_jobs, 14
list_experiments, 77
list_explainabilities, 26
list_explainability_exports, 26
list_exports, 37
list_faces, 66, 70
list_feature_groups, 77
list_filters, 57
list_flow_definitions, 77
list_flywheel_iteration_history, 14
list_flywheels, 14
list_forecast_export_jobs, 26
list_forecasts, 26
list.foundation_models, 8
list_fraudster_registration_jobs, 104
list_fraudsters, 104
list_guardrails, 8
list_hub_content_versions, 77
list_hub_contents, 77
list_hubs, 77
list_human_loops, 6
list_human_task_uis, 77
list_hyper_parameter_tuning_jobs, 77
list_icd10cm_inference_jobs, 17
list_image_versions, 78
list_images, 77
list_imports, 37
list_inference_components, 78
list_inference_events, 45
list_inference_executions, 45
list_inference_experiments, 78
list_inference_recommendations_job_steps,
 78
list_inference_recommendations_jobs,
 78
list_inference_schedulers, 45
list_intent_metrics, 37
list_intent_paths, 37
list_intent_stage_metrics, 37
list_intents, 37
list_key_phrases_detection_jobs, 14
list_label_groups, 45
list_labeling_jobs, 78
list_labeling_jobs_for_workteam, 78
list_labels, 45
list_language_models, 98
list_languages, 101
list_lexicons, 65
list_lineage_groups, 78
list_media_analysis_jobs, 70
list_medical_scribe_jobs, 98
list_medical_transcription_jobs, 98
list_medical_vocabularies, 98
list_metric_attribution_metrics, 57
list_metric_attributions, 57
list_metric_sets, 48
list_model_bias_job_definitions, 78
list_model_card_export_jobs, 78
list_model_card_versions, 78
list_model_cards, 78
list_model_customization_jobs, 8
list_model_explainability_job_definitions,
 78
list_model_metadata, 78
list_model_package_groups, 78
list_model_packages, 78
list_model_quality_job_definitions, 78
list_model_versions, 45
list_models, 45, 78
list_monitor_evaluations, 26
list_monitoring_alert_history, 78
list_monitoring_alerts, 78
list_monitoring_executions, 78
list_monitoring_schedules, 78
list_monitors, 26
list_node_from_template_jobs, 54

list_nodes, 54
 list_notebook_instance.lifecycle_configs,
 78
 list_notebook_instances, 78
 list_package_import_jobs, 54
 list_packages, 54
 list_parallel_data, 101
 list_phi_detection_jobs, 17
 list_pii_entities_detection_jobs, 14
 list_pipeline_execution_steps, 78
 list_pipeline_executions, 78
 list_pipeline_parameters_for_execution,
 78
 list_PIPElines, 78
 list_predictor_backtest_export_jobs,
 26
 list_predictors, 26
 list_processing_jobs, 78
 list_project_policies, 66, 70
 list_projects, 78
 list_provisioned_model_throughputs, 8
 list_raster_data_collections, 88
 list_recipes, 57
 list_recommended_intents, 37
 list_recommenders, 57
 list_resource_catalogs, 78
 list_retraining_schedulers, 45
 list_rx_norm_inference_jobs, 18
 list_schemas, 57
 list_sensor_statistics, 45
 list_sentiment_detection_jobs, 14
 list_session_analytics_data, 37
 list_session_metrics, 37
 list_slot_types, 37
 list_slots, 37
 list_snomedct_inference_jobs, 18
 list_solution_versions, 57
 list_solutions, 57
 list_spaces, 78
 list_speaker_enrollment_jobs, 104
 list_speakers, 104
 list_speech_synthesis_tasks, 65
 list_stage_devices, 78
 list_stream_processors, 67, 70
 list_studio.lifecycle_configs, 78
 list_subscribed_workteams, 78
 list_tags, 78
 list_tags_for_resource, 8, 14, 20, 26, 30,
 33, 37, 45, 48, 54, 57, 70, 88, 95, 98,
 101, 104
 list_targeted_sentiment_detection_jobs,
 14
 list_terminologies, 101
 list_test_execution_result_items, 37
 list_test_executions, 37
 list_test_set_records, 37
 list_test_sets, 37
 list_text_translation_jobs, 101
 list_topics_detection_jobs, 14
 list_training_jobs, 78
 list_training_jobs_for_hyper_parameter_tuning_job,
 78
 list_transcription_jobs, 98
 list_transform_jobs, 78
 list_trial_components, 78
 list_trials, 78
 list_user_profiles, 78
 list_users, 66, 70
 list_utterance_analytics_data, 37
 list_utterance_metrics, 37
 list_vector_enrichment_jobs, 88
 list_vocabularies, 98
 list_vocabulary_filters, 99
 list_watchlists, 104
 list_what_if_analyses, 26
 list_what_if_forecast_exports, 26
 list_what_if_forecasts, 26
 list_workforces, 78
 list_workteams, 78
 lookoutequipment, 43
 lookoutmetrics, 46
 machinelearning, 49
 opt_out Speaker, 104
 panorama, 52
 personalize, 54
 personalizeevents, 58
 personalizeruntime, 60
 polly, 63
 post_content, 40
 post_text, 40
 predict, 51
 provision_device, 54
 put_action_interactions, 60
 put_actions, 60

put_bot, 33
put_bot_alias, 33
put_detector, 30
put_entity_type, 30
put_event_type, 30
put_events, 60
put_external_model, 30
put_feedback, 48
put_intent, 33
put_items, 60
put_kms_encryption_key, 30
put_label, 30
put_lexicon, 65
put_model_invocation_logging_configuration, 8
put_model_package_group_policy, 78
put_outcome, 30
put_project_policy, 66, 70
put_record, 86
put_resource_policy, 14, 45
put_session, 40, 42
put_slot_type, 33
put_users, 60

query_forecast, 22
query_lineage, 78
query_what_if_forecast, 22

recognize_celebrities, 66, 70
recognize_text, 42
recognize_utterance, 42
register_devices, 78
register_package_version, 54
rekognition, 65
remove_application_instance, 54
render_ui_template, 78
resume_resource, 26
retry_pipeline_execution, 79

sagemaker, 71
sagemakeredgemanager, 80
sagemakerfeaturestoreruntime, 82
sagemakergeospatialcapabilities, 86
sagemakermetrics, 89
sagemakerruntime, 91
search, 79
search_associated_transcripts, 37
search_faces, 66, 70
search_faces_by_image, 66, 70

search_raster_data_collection, 88
search_users, 66, 70
search_users_by_image, 66, 70
send_event, 30
send_heartbeat, 82
send_pipeline_execution_step_failure, 79
send_pipeline_execution_step_success, 79
signal_application_instance_node_instances, 54
start_bot_recommendation, 37
start_bot_resource_generation, 37
start_call_analytics_job, 99
start_celebrity_recognition, 67, 70
start_content_moderation, 67, 70
start_data_ingestion_job, 45
start_document_analysis, 95
start_document_classification_job, 14
start_document_text_detection, 95
start_dominant_language_detection_job, 14
start_earth_observation_job, 88
start_edge_deployment_stage, 79
start_entities_detection_job, 14
start_entities_detection_v2_job, 18
start_events_detection_job, 14
start_expense_analysis, 95
start_face_detection, 67, 70
start_face_search, 67, 70
start_flywheel_iteration, 14
start_fraudster_registration_job, 104
start_human_loop, 4, 6
start_icd10cm_inference_job, 18
start_import, 33, 37
start_inference_experiment, 79
start_inference_scheduler, 45
start_key_phrases_detection_job, 14
start_label_detection, 67, 70
start_lending_analysis, 95
start_media_analysis_job, 66, 70
start_medical_scribe_job, 99
start_medical_transcription_job, 99
start_migration, 33
start_monitoring_schedule, 79
start_notebook_instance, 79
start_person_tracking, 67, 70
start_phi_detection_job, 18

start_pii_entities_detection_job, 15
 start_pipeline_execution, 79
 start_project_version, 66, 70
 start_recommender, 57
 start_retraining_scheduler, 45
 start_rx_norm_inference_job, 18
 start_segment_detection, 67, 70
 start_sentiment_detection_job, 15
 start_snomedct_inference_job, 18
 start_speaker_enrollment_job, 104
 start_speech_synthesis_task, 65
 start_stream_processor, 67, 70
 start_targeted_sentiment_detection_job,
 15
 start_test_execution, 37
 start_test_set_generation, 37
 start_text_detection, 67, 71
 start_text_translation_job, 101
 start_topics_detection_job, 15
 start_transcription_job, 99
 start_vector_enrichment_job, 88
 stop_auto_ml_job, 79
 stop_bot_recommendation, 37
 stop_compilation_job, 79
 stop_dominant_language_detection_job,
 15
 stop_earth_observation_job, 88
 stop_edge_deployment_stage, 79
 stop_edge_packaging_job, 79
 stop_entities_detection_job, 15
 stop_entities_detection_v2_job, 18
 stop_evaluation_job, 8
 stop_events_detection_job, 15
 stop_human_loop, 6
 stop_hyper_parameter_tuning_job, 79
 stop_icd10cm_inference_job, 18
 stop_inference_experiment, 79
 stop_inference_recommendations_job, 79
 stop_inference_scheduler, 45
 stop_key_phrases_detection_job, 15
 stop_labeling_job, 79
 stop_model_customization_job, 8
 stop_monitoring_schedule, 79
 stop_notebook_instance, 79
 stop_phi_detection_job, 18
 stop_pii_entities_detection_job, 15
 stop_pipeline_execution, 79
 stop_processing_job, 79
 stop_project_version, 66, 71
 stop_recommender, 57
 stop_resource, 26
 stop_retraining_scheduler, 45
 stop_rx_norm_inference_job, 18
 stop_sentiment_detection_job, 15
 stop_snomedct_inference_job, 18
 stop_solution_version_creation, 57
 stop_stream_processor, 67, 71
 stop_targeted_sentiment_detection_job,
 15
 stop_text_translation_job, 101
 stop_training_document_classifier, 15
 stop_training_entity_recognizer, 15
 stop_training_job, 79
 stop_transform_job, 79
 stop_vector_enrichment_job, 88
 synthesize_speech, 65
 tag_resource, 8, 15, 20, 26, 30, 33, 37, 45,
 48, 54, 57, 71, 88, 95, 99, 101, 104
 textract, 93
 transcribeservice, 96
 translate, 99
 translate_document, 101
 translate_text, 101
 untag_resource, 8, 15, 20, 26, 30, 33, 37, 45,
 48, 54, 58, 71, 88, 95, 99, 101, 104
 update_action, 79
 update_active_model_version, 45
 update_adapter, 95
 update_alert, 48
 update_anomaly_detector, 48
 update_app_image_config, 79
 update_artifact, 79
 update_batch_prediction, 51
 update_bot, 37
 update_bot_alias, 37
 update_bot_locale, 37
 update_bot_recommendation, 37
 update_call_analytics_category, 99
 update_campaign, 58
 update_cluster, 79
 update_cluster_software, 79
 update_code_repository, 79
 update_context, 79
 update_data_source, 51
 update_dataset, 58

update_dataset_entries, 66, 71
update_dataset_group, 26
update_detector_version, 30
update_detector_version_metadata, 30
update_detector_version_status, 30
update_device_fleet, 79
update_device_metadata, 54
update_devices, 79
update_domain, 79, 104
update_endpoint, 15, 79
update_endpoint_weights_and_capacities,
 79
update_evaluation, 51
update_event_label, 30
update_experiment, 79
update_export, 37
update_feature_group, 79
update_feature_metadata, 79
update_flywheel, 15
update_guardrail, 8
update_hub, 79
update_image, 79
update_image_version, 79
update_inference_component, 79
update_inference_component_runtime_config,
 79
update_inference_experiment, 79
update_inference_scheduler, 45
update_intent, 37
update_label_group, 45
update_list, 30
update_medical_vocabulary, 99
update_metric_attribution, 58
update_metric_set, 48
update_ml_model, 51
update_model, 30, 45
update_model_card, 79
update_model_package, 79
update_model_version, 30
update_model_version_status, 30
update_monitoring_alert, 79
update_monitoring_schedule, 79
update_notebook_instance, 80
update_notebook_instance_lifecycle_config,
 80
update_parallel_data, 101
update_pipeline, 80
update_pipeline_execution, 80
update_project, 80
update_provisioned_model_throughput, 8
update_recommender, 58
update_resource_policy, 37
update_retraining_scheduler, 45
update_rule_metadata, 30
update_rule_version, 30
update_slot, 37
update_slot_type, 37
update_space, 80
update_stream_processor, 67, 71
update_test_set, 37
update_training_job, 80
update_trial, 80
update_trial_component, 80
update_user_profile, 80
update_variable, 30
update_vocabulary, 99
update_vocabulary_filter, 99
update_watchlist, 104
update_workforce, 80
update_workteam, 80
voiceid, 102