

# Package ‘poisonfrogs’

November 24, 2025

**Title** Color Palettes Inspired by Neotropical Poison Frogs

**Version** 1.0.2

**Description** A collection of color palettes inspired by the enormous diversity of skin colors in Neotropical poison frog species. Suitable for use with 'ggplot2' and base R graphics.

**URL** <https://laurenocConnellab.github.io/poisonfrogs/>

**BugReports** <https://github.com/laurenocConnellab/poisonfrogs/issues>

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**Depends** R (>= 2.10)

**Imports** ggplot2 (>= 3.4.0), lifecycle, rlang

**Suggests** testthat (>= 3.0.0), gapminder, ggribbles, scales, tibble

**Config/testthat/edition** 3

**Config/Needs/website** rmarkdown

**NeedsCompilation** no

**Author** Camilo Rodríguez [aut, cre],  
Lauren O'Connell [aut]

**Maintainer** Camilo Rodríguez <camo.rodriguez@gmail.com>

**Repository** CRAN

**Date/Publication** 2025-11-24 18:30:02 UTC

## Contents

poisonfrogs . . . . .	2
poison_palette . . . . .	2
poison_palettes_names . . . . .	3
scale_color_poison . . . . .	4

<b>Index</b>	<b>7</b>
--------------	----------

---

poisonfrogs

*Colour Palettes of Neotropical Poison Frogs*

---

### Description

A collection of color palettes inspired by the enormous diversity of skin colors in Neotropical poison frog species. Suitable for use with 'ggplot2' and base R graphics.

### Author(s)

**Maintainer:** Camilo Rodríguez <camo.rodriguez@gmail.com>

Authors:

- Lauren O'Connell <loconnel@stanford.edu>

### See Also

Useful links:

- <https://laurenocnelloab.github.io/poisonfrogs/>
- Report bugs at <https://github.com/laurenocnelloab/poisonfrogs/issues>

---

poison\_palette

*Plot and print poison frog color palettes.*

---

### Description

Visualize colors and print hexcodes from a poison frog color palette.

### Usage

```
poison_palette(  
  name,  
  n = NULL,  
  type = c("discrete", "continuous"),  
  direction = 1,  
  alpha = NULL,  
  return = c("plot", "vector")  
)
```

**Arguments**

name	Character. Name of poison frog palette (one of <code>poison_palettes_names()</code> ).
n	Integer (optional). Number of colours to use. Defaults to the palette length (max. $n = 5$ ) for <code>type = "discrete"</code> and 256 for <code>type = "continuous"</code> .
type	Either <code>"discrete"</code> or <code>"continuous"</code> .
direction	Integer. 1 for forward, -1 for reversed order.
alpha	Optional numeric in $[\emptyset, 1]$ . Uniform transparency applied to all colours.
return	Either <code>"plot"</code> (default) to show a tile plot with hex labels, or <code>"vector"</code> to return a character vector of hex colours.

**Value**

If `return = "plot"`, a `ggplot2` object. If `return = "vector"`, a character vector of hex colours.

**Examples**

```
# Show a palette as tiles (default)
poison_palette("Ramazonica")

# Reverse order and show only 4 colours
poison_palette("Ramazonica", n = 4, direction = -1)

# Get a vector with the palette hex codes
cols <- poison_palette("Ramazonica", return = "vector")

# Continuous gradient preview (16 swatches)
poison_palette("Osotokiki", type = "continuous", n = 16)
```

---

`poison_palettes_names` *List the names of available color palettes inspired in poison frogs and other frog species.*

---

**Description**

List the names of available color palettes inspired in poison frogs and other frog species.

**Usage**

```
poison_palettes_names()
```

**Value**

A character vector of palette names.

**Examples**

```
poison_palettes_names()
```

---

scale\_color\_poison      *Poison frog color scales for ggplot2*

---

### Description

The poison scales provide color maps inspired by the diverse colors of Neotropical poison frogs. For **discrete** data it uses `ggplot2::discrete_scale()`, and for **continuous** data it builds a smooth gradient with `ggplot2::scale_color_gradientn()`.

### Usage

```
scale_color_poison(
  name,
  type = c("discrete", "continuous"),
  direction = 1,
  alpha = NULL,
  ...
)
```

```
scale_colour_poison(
  name,
  type = c("discrete", "continuous"),
  direction = 1,
  alpha = NULL,
  ...
)
```

```
scale_fill_poison(
  name,
  type = c("discrete", "continuous"),
  direction = 1,
  alpha = NULL,
  ...
)
```

### Arguments

name	Character. Name of the poison frog palette to use one of <code>poison_palette_names()</code> .
type	Either "discrete" or "continuous". Selects which kind of ggplot2 scale is constructed.
direction	Integer. 1 for the palette in its stored order, -1 to reverse it.
alpha	Optional numeric in $[0, 1]$ . Applies a uniform transparency to all colors (both discrete and continuous modes).
...	Additional arguments passed to the underlying ggplot2 scale.

## Details

- **Discrete:** relies on an internal function factory `poison_pal()` that returns `n` colors (max. `n = 5`) on demand for `ggplot2::discrete_scale()`.
- **Continuous:** generates a 256-color gradient via `poison_palette()` (type "continuous") and passes it to `ggplot2::scale_color_gradientn()`.

## Value

A `ggplot2` scale object.

## See Also

`poison_palette()`, `poison_pal()`

## Examples

```
require(ggplot2)
require(gapminder)
require(ggribbles)
require(tibble)
require(scales)

# Using `scale_color_poison()` with discrete scale
ggplot(gapminder, aes(x = lifeExp, y = log(gdpPercap), colour = continent)) +
  geom_point(alpha = 0.2) +
  scale_color_poison(name = "Ramazonica", type = "discrete") +
  stat_smooth() +
  facet_wrap(. ~ continent, scales = "free") +
  theme_minimal(21, base_line_size = 0.2) +
  theme(
    legend.position = "none",
    strip.background = element_blank(),
    strip.placement = "outside"
  )

# Using `scale_color_poison()` with continuous scale
ggplot(mtcars, aes(wt, mpg, colour = disp)) +
  geom_point(size = 3) +
  scale_color_poison("Ramazonica", type = "continuous", direction = -1) +
  stat_smooth(col = "black") +
  theme_classic(base_size = 32, base_line_size = 0.5)

# Using `scale_fill_poison()` with discrete scale
ggplot(gapminder, aes(x = continent, y = lifeExp, fill = continent)) +
  geom_violin(trim = FALSE, alpha = 0.75) +
  geom_jitter(
    shape = 21,
    position = position_jitter(0.1),
    alpha = 0.3,
    size = 0.8,
```

```

  bg = "grey"
) +
stat_summary(
  fun = mean,
  geom = "point",
  size = 1.5,
  color = "black",
  alpha = 0.6
) +
theme_classic(base_size = 32, base_line_size = 0.5) +
scale_fill_poison(
  name = "Ramazonica",
  type = "discrete",
  alpha = 0.95,
  direction = -1
) +
theme(legend.position = "none") +
xlab(NULL)

df_nottem <- tibble(year = floor(time(nottem)),
                   month = factor(month.abb[cycle(nottem)]),
                   levels = month.abb,
                   temp = as.numeric(nottem))

# Using `scale_fill_poison()` with continuous scale
ggplot(df_nottem, aes(x = temp, y = month, fill = stat(x))) +
  geom_density_ridges_gradient(scale = 2, rel_min_height = 0.01) +
  scale_fill_poison(
    name = "Ramazonica",
    type = "continuous",
    alpha = 0.95,
    direction = 1
  ) +
  labs(
    fill = "eF") +
  theme_light(base_size = 26, base_line_size = 0.5) +
  theme(
    legend.position = "right",
    legend.justification = "left",
    legend.margin = margin(0,0,0,0),
    legend.box.margin = margin(-20,-20,-20,-20)
  )

```

# Index

`ggplot2::discrete_scale()`, [4](#), [5](#)  
`ggplot2::scale_color_gradientn()`, [4](#), [5](#)

`poison_palette`, [2](#)  
`poison_palettes_names`, [3](#)  
`poisonfrogs`, [2](#)  
`poisonfrogs-package (poisonfrogs)`, [2](#)

`scale_color_poison`, [4](#)  
`scale_colour_poison`  
    (`scale_color_poison`), [4](#)  
`scale_fill_poison (scale_color_poison)`,  
    [4](#)