

Package ‘simplecolors’

August 31, 2023

Title Access Color Names Using a Standardized Nomenclature

Version 0.1.2

Description A curated set of colors that are called using a standardized syntax: saturation + hue + lightness. For example, “brightblue4” and “mutedred2”. Functions exist to return individual colors by name or to build palettes across or within hues. Most functions allow you to visualize the palettes in addition to returning the desired hex codes.

URL <https://github.com/rjake/simplecolors>

BugReports <https://github.com/rjake/simplecolors/issues>

Imports colorspace, dplyr, forcats, ggplot2, magrittr, stats, stringr

Suggests knitr, rmarkdown, testthat, covr, devtools, spelling

Depends R (>= 3.1.0)

License GNU General Public License

VignetteBuilder knitr

Language en-US

LazyData true

RoxygenNote 7.2.3

Encoding UTF-8

NeedsCompilation no

Author Jake Riley [aut, cre]

Maintainer Jake Riley <rjake@sas.upenn.edu>

Repository CRAN

Date/Publication 2023-08-31 04:40:07 UTC

R topics documented:

color_table	2
sc	3
sc_across	3

sc_within	4
show_colors	5
simplecolors	5

Index	7
--------------	----------

color_table	<i>Table of available colors</i>
-------------	----------------------------------

Description

This is a list of simplified color names

Usage

color_table

Format

A data frame with 200 observations and 15 variables

H360 hue on a 0-360 scale

L1 lightness on a 0-1 scale

S1 saturation on a 0-1 scale

light the light value used in the package, 0-7

color the base color name (hue), red, cyan, etc.

letter the first letter of the color, for building palettes

sat the saturation value used in the package, "bright", "muted", "dull", or blank ""

color_sat the color + the saturation, ex: "brightblue", "dullred"

color_name the final unique name: color_sat + lightness, ex: "brightblue2", "mutedorange3"

H1 hue on a 0-1 scale

hex the hex code of the color

R the red of the RGB value

G the green of the RGB value

B the blue of the RGB value

H255 for convenience as some HLS selection tools use a 0-255 scale

sc *Specify color(s) by name*

Description

Specify color(s) by name

Usage

```
sc(...)
```

Arguments

... the unique color names used in the package, ex: "brightred5", "grey4", "dull-blue2"

Examples

```
sc("violet4", "brightteal3")
```

sc_across *Generates a palette within across hues*

Description

Generates a palette within across hues

Usage

```
sc_across(palette = "ROYGTBVPgy", light = 3, sat = "", return = NULL)
```

Arguments

palette the first letter of each hue to include
 light the lightness value to hold constant (1:7)
 sat the saturation value to hold constant ("bright", "muted", "dull", "")
 return defaults to returning hex codes but can also return a table or plot of the generated palette

See Also

Other palettes: [sc_within\(\)](#)

Examples

```

sc_across(palette = "B0")
sc_across(palette = "B0", sat = "bright", return = "table")
sc_across(palette = "B0", sat = "bright", return = "plot")
sc_across(palette = "RBTVPgy", light = 4, return = "plot")

```

sc_within	<i>Generates a palette within 1 hue</i>
-----------	---

Description

Generates a palette within 1 hue

Usage

```

sc_within(hue, light = c(2:5), sat = "", return = NULL)

sc_red(light = 2:5, sat = "", return = NULL)

sc_orange(light = 2:5, sat = "", return = NULL)

sc_yellow(light = 2:5, sat = "", return = NULL)

sc_green(light = 2:5, sat = "", return = NULL)

sc_teal(light = 2:5, sat = "", return = NULL)

sc_blue(light = 2:5, sat = "", return = NULL)

sc_violet(light = 2:5, sat = "", return = NULL)

sc_pink(light = 2:5, sat = "", return = NULL)

sc_grey(light = 2:5, sat = "", return = NULL)

```

Arguments

hue	ex: "red", "blue", "violet"
light	the lightness of the color, ex: 1:5
sat	the saturation of the color, ex: "bright", "muted", "dull" or "" (base)
return	defaults to returning hex codes but can also return a table or plot of the generated palette

See Also

Other palettes: [sc_across\(\)](#)

Examples

```
sc_within("violet", 1:3)
sc_within("violet", 1:5, "bright" , return = "table")
sc_within("violet", 2:4, c("bright", "muted"), return = "plot")
```

show_colors

Show all available colors

Description

Plots all available color values.

Usage

```
show_colors(labels = FALSE)
```

Arguments

labels logical TRUE (default) will plot the color with color names, FALSE will plot the colors only

Details

Labels can be added by using the argument labels = TRUE

Value

Returns a plot object
ggplot

Examples

```
show_colors()
```

simplecolors

simplecolors: A package for accessing color names using a standardized nomenclature

Description

The simplecolors package provides two categories of functions: color names and color palettes

Color names

The sc() function is the main way to access color names. Colors can be called by including them as comma separated string values. For example: sc("brightblue4", "mutedred2")

Color palettes

There are several functions that are prefixed with "sc_". These generate palettes of colors and can return hex codes (default), a table, or a plot showing the colors selected.

Author(s)

Maintainer: Jake Riley <rjake@sas.upenn.edu>

See Also

Useful links:

- <https://github.com/rjake/simplecolors>
- Report bugs at <https://github.com/rjake/simplecolors/issues>

Index

- * **datasets**

- color_table, 2

- * **palettes**

- sc_across, 3

- sc_within, 4

color_table, 2

sc, 3

sc_across, 3, 4

sc_blue (sc_within), 4

sc_green (sc_within), 4

sc_grey (sc_within), 4

sc_orange (sc_within), 4

sc_pink (sc_within), 4

sc_red (sc_within), 4

sc_teal (sc_within), 4

sc_violet (sc_within), 4

sc_within, 3, 4

sc_yellow (sc_within), 4

show_colors, 5

simplecolors, 5

simplecolors-package (simplecolors), 5